



Model: USB-4COMi-SI-M

4 Port USB to Quad RS-422 485 Optically Isolated Adapter

The USB-4COMi-SI-M Serial Adapter instantly adds four RS-422, or RS-485 serial communication ports to your system while offering optical isolation and surge protection.



Specifications

| | |
|------------------|--|
| Serial Interface | RS422/485 port, optical isolated |
| Ports | 4 |
| Speed | Up to 921.6kbps |
| Signals | RS422 TxD+/-, RxD+/-, RTS+/-, CTS+/-, GND RS485 Data+/-, GND |
| Available Modes | RS422 full duplex, RS485 4-wire, full duplex, RS485 2-wire, half duplex, with echo RS485 2-wire, half duplex, without echo |
| USB Interface | USB 2.0 |
| Power | External power supply 5V DC required. Adapter included 12V not possible. |
| Driver | Windows XP, 2003 Server, Vista, Linux (Kernel 2.4 and up built-in) |
| Connectors | 4 DB9 male |
| Dip Switches | External 4-pin |
| Dimensions | 167 x 99 x 29 mm (WxLxH), 189 x 102 x 30 mm (with DB9 connector and ears) |
| Environmental | Operating Temperature 0 to 55 °C (32 to 131 °F) Operating Humidity 5 to 95% RH Storage Temperature -20 to 75 °C (-4 to 167 °F) |

| Features | Product Information |
|---|---|
| <ul style="list-style-type: none"> • DIN-Rail mountable • 4 x RS422/485 ports • Optical isolated • Speed up to 921.6kbps • External power supply • Metal case | <p>Product Name: USB-4COMi-SI-M</p> <p>Packing List: USB-4COMi SI-M, USB cable 0,9m, Power adapter, CD, English Documentation</p> <p>Optional Accessories: N/A</p> |