USB-2COM-M Technical Data Sheet

www.coolgear.com



Model: USB-2COM-M

2 PORT USB to Serial RS-232 DB-9 Adapter Industrial Metal Housing

Industrial USB to Serial adapter with a rugged metal case, which allows the addition of two RS-232 communication ports to your computer by connecting to a single host USB port. Designed with terminal 2-wire power option if needed.



| Specifications | | |
|------------------|--|--|
| Serial Interface | RS232 | |
| Ports | 2 | |
| Speed | Up to 921.6kbps | |
| RS232 Signals | TxD, RxD, RTS, CTS, DTR, DSR, DCD, GND | |
| USB Interface | USB 1.0/1.1 compliant, USB 2.0 compatible | |
| Power | Bus-powered, No external power adapter required | |
| Driver | Windows XP, 2003 Server, Vista, Linux (Kernel 2.4 and up built-in) | |
| Connectors | 2 DB9 male | |
| Dimensions | 57 x 72 x 22 mm (W×L×H), 82 x 82 x 22 mm with DB9 connector and ears | |
| Environmental | Operating Temperature 0 to 55 °C (32 to 131 °F) Operating Humidity 5 to 95% RH Storage Temperature -20 to 75 °C (-4 to 167 °F) | |

| Features • Metal case | Product Information | |
|--|-----------------------|---|
| DIN-Rail mountable | Product Name: | USB-2COM-M |
| 2 x RS232 DB9 male portSpeed up to 921.6 kbps | Packing List: | USB-2COM-M, USB cable 0,9m, CD, English Documentation |
| No external power supply | Optional Accessories: | N/A |
| | | |
| | | |
| | | |