



Model: USBG-12U2ML

Industrial 12-Port USB 2.0 Powered Hub for PC-Mac – DIN Rail Mount

12-Port USB 2.0 powered hi-speed hub enabling you to connect 12 additional USB peripherals to your system. Industrial-grade metal chassis supporting rugged use and is backward compatible with USB 1.0/1.1.



Specifications

Compliance	USB 2.0 compliant – Backward compatible with USB 1.0/1.1
Speed	480Mbps High Speed, 12 Mbps Full-Speed USB, 1.5Mbps Low Speed
Power	3-Pin Terminal Block Connector supplies 7~24V – AC Power Adapter , Supports Self-Powered Mode
Port Type	USB Type-A Female, USB Type-B Female
Number of Ports	12 USB 2.0 Type-A Downstream Ports, 1 USB Type-B Upstream Port
LED Indicators	LED Port and Power Status
Chip	Built-in 4X GL-852 Multi-TT Chip USB 2.0 Hub Controller
Connections	Multi Transaction Translator per Hub and Supports 12 Concurrent Non-periodic Transactions
Housing	Industrial Grade metal chassis
Environmental	Operating Temperature: 0 to 55 °C 32 to 131 °F Operating Humidity 5 to 95% RH Storage Temperature: -20 to 85 °C (-4 to 185 °F)

Features

- Complaint with USB Specification Revision 2.0
- Rigid and Wall Mountable Metal Case
- Supports High-speed and or Full-speed Packet
- Built-in Multi-TT Chip USB 2.0 Hub Controller
- Provides 12 Downstream Facing Ports
- Supports Self Power Mode
- Protocol Sequencer for Endpoint 0/1

Product Information

- Product Name:** USBG-12U2ML
- Packing List:** USBG-12U2ML Hub, 3ft USB High Speed Cable, Power Plug for optional AC power supply, User Manual
- Optional Accessories:** [External Power Supply](#) sold separately