

USBG-232FT-1 Technical Data Sheet

www.coolgear.com



Model: USBG-232FT-1

Dual Port RS-232 USB to Serial Plug-in Adapter

The USBG-232FT-1 is a Dual Port RS-232 USB to Serial adapter that allows you to add two RS-232 serial ports to your computer by connecting to a single USB port. Adapter includes a 3 foot USB extension cable.



Specifications

•		
Compliance	USB 1.0/1.1 compliant, USB 2.0 compatible	
Speed	12 Mbps, Full-Speed USB	
FIFO	128 byte transmit FIFO – 384 Receive FIFO	
Port Type	RS-232	
Number of Ports	2 DB-9 Ports	
ESD Protection	10KV	
Baud Rates	300 bps to 921.6k bps	
RS-232 Signals	DCD, RxD, TxD, DTR, GND, DSR, RTS, CTS, RI	
Data Bits	5, 6, 7, 8	
Stop Bits	1, 1.5, 2	
Parity	None, Even, Odd, Space, Mark	
Housing	Plastic, ABS	
Power	Bus Powered	
Environmental	Operating Temperature: 0 to 55 °C 32 to 131 °F) Humidity 5 to 95% RH Storage Temperature: -20 to 75 °C (-4 to 167 °F)	

Features

Product Information

Adds two serial RS232 Ports	Product Name:	USBG-232FT-1
 Installed as a standard Windows COM Port Full RS-232 modem control signals 	Packing List:	USBG-232FT-1 adapter, 3ft USB Extension Cable, Driver Disk, User Manual
 LED status indicators for TxD and RxD 	Optional Accessories:	N/A
 Plug and Play device connection 		

- COM port assignment can be changed
- 10k Surge Protection