

Model: USBG-232MINI

Mini USB RS-232 Serial Adapter – DB-9 Male



The USBG-232MINI Mini USB RS-232 to Serial Adapter can be utilized through an existing USB Port to work with your legacy serial connections. It's great for newer technologies with no serial port connections.



Specifications

Serial Interface	RS232 port
Ports	1
Speed	12 Mbps, Full-Speed USB
Baud Rates	300 bps to 921.6k bps
RS232 Signals	TxD, RxD, RTS, CTS, DTR, DSR, DCD, GND, RI
Parity	None, Even, Odd, Space, Mark
Flow Control	RTS/CTS, XON/XOFF
Compliance	USB 1.0/1.1 compliant, USB 2.0 compatible
Power	Bus powered, No external power supply
FIFO	128 byte transmit FIFO – 384 receive FIFO
ESD Protection	10KV
Driver	Windows 2000 to Windows 8, Windows Server 2000 to 2008 R2, Both x86 and x64 Editions Linux (Kernel 2.4 and up built-in)
Chassis	Plastic, ABS
Environmental	Operating Temperature 0 to 55 °C (32 to 131 °F) Operating Humidity 5 to 95% RH Storage Temperature -20 to 75 °C (-4 to 167 °F)

Features

- Installs as Windows COM Port
- Includes USB cable
- LED status indicators for TxD and RxD
- 10KV Surge Protection
- Powered by USB port, no external power needed
- COM Port number assignment can be changed
- Baud Rates of up to 921.6Kbps

Product Information

Product Name: [USBG-232MINI](#)
Packing List: USBG-232MINI Adapter, USB cable
Optional Accessories: N/A