CoolGear, Inc.

5120 110th Ave N Clearwater, FL 33760 P: +1-727-209-1300 F: +1-727-209-1302 www.coolgear.com

<u>USBG-4U2ML</u> Industrial 4-Port USB 2.0 Powered Hub for PC-MAC DIN-RAIL Mount



Specifications		
USB Interface	USB 2.0	
Port Connections	1 Upstream type "B", 4 Downstream	
Speed	Supports 480Mbps, 12Mbps and 1.5Mbps Speed	
Available Power Modes	Bus Power Self power source (+7~24VDC from 3-pin Terminal Blocks)	
LEDs	Power LED, Port Activity (Downstream)	
Construction	Rigid Industrial Metal Case	
Color	Black	
Mountable	Wall, Din-Rail	
Dimensions	4.50"(L) x 2.26"(W) x 1.03"(H), (11.45 x 5.73 x 2.63 cm)	
OS Support	Windows 2000, 2003, CE, Vista, Windows 7, and Windows 8, Linux and Mac OS 10.X	
Environmental	Operating Temperature 0 to 55 °C (32 to 131 °F) Operating Humidity 5 to 95% RH Storage Temperature Storage Temp: -20°C to 85°C (-4 to 185° F)	
Current Certifications	RoHS	

Features • Compliant with USB specification Rev 2.0	Product Information	
 Rigid and Wall-mountable Metal Case 	Product Name:	USBG-4U2ML
 Supports High-Speed and or Full-Speed Packet Protocol Sequencer for Endpoint 0/1 Provides 4 Downstream facing ports 	Packing List:	Industrial 4-Port USB 2.0 Powered Hub, 3- foot Hi-Speed USB 2.0 certified A to B cable, Mounting Brackets
Supports Self-powered and Bus-powered mode	Optional Accessories:	N/A

