CoolGear, Inc.

5120 110th Ave N Clearwater, FL 33760 P: +1-727-209-1300 F: +1-727-209-1302 www.coolgear.com

<u>USBG-4U3ML</u> USB 3.0 4-Port Industrial Hub Metal Case



Specifications			
USB Interface	Compliant with USB 3.0, compatible with USB 2.0/1.1		
Port Connections	1 Upstream type "B", 4 Downstream, Screw lock all USB ports		
Speed	5Gbps (Super-speed), 480Mbps (High-speed), 12Mbps Full-speed) and 1.5Mbps (Low-speed) Speed		
Power	Self power source (+7~24VDC from 2-pin Terminal Blocks), supplies up to 900mA USB Bus Power for each Down-stream port		
Surge Protection	350-Watt each port		
LEDs	Power LED		
Construction	Rigid Industrial Metal Case		
Color	Black		
Mountable	Wall, Din-Rail		
Dimensions	5.61"(L) x 2.56"(W) x 1.03"(H), (14.25 x 6.52 x 2.63 cm)		
OS Support	Windows 2000, 2003, CE, Vista, Windows 7, and Windows 8, Linux and Mac OS 10.X		
Environmental	Operating Temperature 0 to 55°C (32 to 131°F) Operating Humidity 5 to 95% RH Storage Temperature: -20°C to 85°C (-4 to 185° F)		
Current Certifications	RoHS		

Features • Compliant with USB specification Rev 3.0	Product Information	
Rigid and Wall-mountable Metal Case	Product Name:	USBG-4U3ML
 Supports Super-Speed, High-Speed, Full-Speed, and Low-Speed 350 Watt Surge Protection each port 	Packing List:	Industrial 4-Port USB 3.0 Hub, 3-foot Hi- Speed USB 3.0 certified A to B cable, User Manual
Support USB Battery Charging: CDP and DCP modes Supports USB Scrow Lock Cable Mechanism	Optional Accessories:	N/A
Supports USB Screw-Lock Cable Mechanism		

