



Model: XC-232-C

Dual Port USB to Serial RS-232 DB-9 Adapter – FTDI Chip

This USB to Serial Dual Port Adapter converts your USB port into two 9-pin male RS-232 serial ports capable of speeds up to 920Kbps. It features a rugged plastic housing with built-in LED status indicators for TxD and RxD.



Specifications

Serial Interface	RS232 port
Ports	2
Speed	12 Mbps, Full-Speed USB
Baud Rates	300 bps to 921.6k bps
RS232 Signals	TxD, RxD, RTS, CTS, DTR, DSR, DCD, GND, RI
Compliance	USB 1.0/1.1 compliant, USB 2.0 compatible
Power	Bus powered, No external power supply
Connectors	2 DB9 male
ESD Protection	10KV
Driver	Windows 2000 to Windows 8, Windows Server 2000 to 2008 R2, Both x86 and x64 Editions Linux (Kernel 2.4 and up built-in)
Chassis	Plastic, ABS
Environmental	Operating Temperature 0 to 55 °C (32 to 131 °F) Operating Humidity 5 to 95% RH Storage Temperature -20 to 75 °C (-4 to 167 °F)

Features

- Installs as Windows COM Port
- Full RS232 modem control
- 2 x RS232 Ports
- 10KV Surge Protection
- Powered by USB port, no external power needed
- COM Port number assignment
- Baud Rates of up to 921.6Kbps

Product Information

Product Name: [XC-232-C](#)
Packing List: XC-232-C Adapter, USB cable, user manual, and Driver Disk
Optional Accessories: N/A