

Model: CG-1600i-RM

Industrial 16-Port Rack-Mountable USB 2.0 Hub



Industrial 16-Port USB 2.0 Rack Mountable Hub is a rugged, industrial-grade metal hub. The hub is compliant with USB 2.0 specification and can expand one USB port into 16 high-efficient USB 2.0 ports. It is designed for the use in industrial applications under tough working environments.



Specifications

USB Interface	USB 2.0
Ports	16 Downstream, 1 Upstream
LEDs	Power 1, Port status 16
Power Supply	Input: Self-powered 90V AC to 264V AC Output Voltage: +5V DC per port Output Current: 500mA (max)
Mechanical	Housing: Rack-mountable Metal Case Weight: 1100 g
Environmental	Operating Temperature -40°C to 70 °C (-40°F to 158 °F) Operating Humidity 0 to 90% RH Noncondensing Storage Temperature -40 °C to 85 °C (-40 °F to 185 °F)
Safety Approvals	CE, FCC
Dimensions	427mm x 144mm x 44mm (W x L x H) 449mm x 144mm x 44mm with ears.
Transfer	USB 1.1 and USB 2.0 transfer speeds (1.5 ~ 480Mbps), automatic link and speed detection.
OS Support	Windows XP, 2000, 2003, CE, Vista, Windows 7, and Windows 8 Linux and Mac OS 10.X

Features

- Plug-and-Play, no software or drivers required.
- 15KV ESD immunity for serial interface protected.
- All USB connectors with screw holes for lock the USB cable.
- Common mode filtering on all data lines.
- Supports wide ambient temperature operation.
- Suitable for DIN-rail mounting.
- All USB ports with Screw lock holes.

Product Information

Product Name: CG-1600i-RM
Packing List: CG-1600i-RM Hub
Optional Accessories: