



# 1-Port USB to Serial Adapter (RS-232/422/485), DIN-rail



Model No. USB-COMi-PRO



- Adds one RS-232, or RS-422, or RS-485 serial port via USB connection.
- Software configuration for easy RS-232, RS-422, RS-485 mode settings.
- *Remote Serial Port Sharing*: allows remote access to USB serial port regardless of its physical location.
- Software configuration of serial port type, operation modes, termination resistors and Biasing.
- 512 byte transmit buffer and 512 byte receive buffer using buffer smoothing technology for high data throughput.
- ESD surge protection of 15 KV.
- Monitor LEDs of Power, Tx/D, Rx/D indicating power & port status.

Interested? [LEARN MORE →](#)



## Questions? Speak to an engineering expert today!

Our on site engineers are ready to help you with your build.

☎ [1-727-209-1300](tel:1-727-209-1300) (Local) ✉ [expert@coolgear.com](mailto:expert@coolgear.com)



**We Speak Your Speak** - When you reach out to our support, you'll find yourself in the hands of a solution-oriented, knowledgeable expert ready to answer whatever question you throw at them. Go ahead, test us.

**We're Ready For Integration, Every Time.** - Coolgear streamlines the task of selecting charging and connectivity products. For over 20 years our rugged, off-the-shelf USB hubs and serial products are ready to go for your next project.

**Within every great machine, lives Coolgear.** - At Coolgear, we're just as passionate about building great products as you are. That's why we aim to meet or exceed your build specs every time.,

**Advanced Engineering** - Coolgear painstakingly sources high-quality components, oversees all manufacturing methods, and conducts rigorous testing to ensure all our products are industrial-grade. This means greater duty cycle, zero data loss, and longer lasting builds. We promise.,

# PRODUCT SPECIFICATIONS

Looking for product documentation?  
[View CAD Models, Data sheet and Drawings here >](#)



Serial Attributes	Performance	ESD Protection	15KV Surge Protection for Each Port
	Hardware	LED Indicators	?
	Software	OS Support	Windows 10, 8, Windows 7, Windows Vista 32-bit, Vista 64-bit, Windows Server 2016, 2012, 2008, 2003, XP; Linux 3.2 and greater; Mac OS-X
	USB	Serial Standards	RS232/RS422/RS485
		Serial Ports	1
		Upstream USB Ports	1 Type-B Female USB
	Mechanical	Supported Data Speed	300bps to 3Mbps
		Item Dimensions (L × W × H)	57mm x 76mm x 23mm
		Item Weight	4.7 oz.
	Other Data	Mounting Style	Surface Mount
		UPC	045079162907
		Weight	0.5375 lbs
	Dimensions	5.04 × 4.08 × 2.57 in	

## Ready to Buy? Let's get to work!

Purchase order lets set you up.

Online with Credit card Orders shipped same day!

\*orders placed prior to 3:30pm EST

 **1-888-688-2188 (Toll free)**

 **[sales@coolgear.com](mailto:sales@coolgear.com)**