

10 Port USB 3.2 Gen 1 Hub w/ ESD Surge Protection & Screw Locking Ports



Industrial Grade | +12~24V DC Input | Surge Protection | Surface Mountable | DIN Rail | 5 Gbps | Screw Lock

Model No. CG-10U3AML



- Protect Your Equipment: The 10-port USB 3.2 Gen 1 features 350 Watts of surge protection and 15kV ESD protection to keep your connected peripherals safe.
- Super Fast Speeds: This USB hub is 3.2 Gen 1 compliant, ensuring super-fast 5Gbps data transfer speeds. It supports super speed, high speed and full speed which enables it to be compatible with USB 2.0 / 1.1.
- Superior Build Quality: Housed in a rugged steel chassis with built in mountable flanges, the 10-port hub is perfect for installations in offices, labs, warehouses, heavy machinery, automation equipment, and other industrial applications.
- Secure Connections: Screw locking ports help ensure reliable connections.
- Upstream: 1 USB port, Type B connector, Screw-lock type
- Downstream: 10 USB ports, Type A connectors, Screw-lock type
- Power Connector: 2-Pin Terminal Block
- Mounting Options: Wall, Surface, and DIN Rail

Interested? LEARN MORE >

Questions? Speak to an engineering expert today!

Our on site engineers are ready to help you with your build.

¹ 1-727-209-1300 (Local) **expert@coolgear.com**



We Speak Your Speak - When you reach out to our support, you'll find yourself in the hands of a solution-oriented, knowledgeable expert ready to answer whatever question you throw at them. Go ahead, test us. **We're Ready For Integration, Every Time.** - Coolgear streamlines the task of selecting charging and connectivity products. For over 20 years our rugged, off-the-shelf USB hubs and serial products are ready to go for your next project.

Within every great machine, lives Coolgear. - At Coolgear, we're just as passionate about building great products as you are. That's why we aim to meet or exceed your build specs every time.,

Advanced Engineering - Coolgear painstakingly sources high-quality components, oversees all manufacturing methods, and conducts rigorous testing to ensure all our products are industrial-grade. This means greater duty cycle, zero data loss, and longer lasting builds. We promise.,

PRODUCT SPECIFICATIONS

Looking for product documentation?

View CAD Models, Data sheet and Drawings here >



Operating Temperature 0°C to 70°C (32°F to 158°F)

Environmental Storage Temperature -20 to 75°C (-4 to 167°F)

Humidity 5% ~ 95% (non-condensing)

ESD Protection 15KV Surge Protection for Each Port

Performance Max Data Transfer Rate 5Gbps

Over Voltage Protection Y per buck

Chipset GL 3523

Hardware Charging Protocols

BC 1.2, Charging Downstream Port (CDP), Dedicated

Charging Port (DCP)

LED Indicators Power

Product

Mechanical

Information 1 year from date of purchase

Input Voltage +7~24V DC

Over Voltage Protection Y per buck

Power Source 2-Pin Terminal Block, AC Adapter Not Included

Idle Consumption 0.75mA @ 12V Terminal Power, 0.76mA @ 24V Terminal

Power, 46.42mA - Bus Power

External Power Required No

Software OS Support Win 11, Linux, Mac OSX, Win 10, Win 7, Win 8

What's in the Box Package Contents

2-Pin Terminal Block, DIN Rail Clip(s), Hub, Screw Pack, USB-

A to Screw Lock USB-B Cable

USB Type USB 3.2 Gen 1

Upstream USB Ports 1 Type-B Female USB USB

Downstream USB Ports 10 Type-A Female USB

Screw Lock Compatible Yes

Color Black

Item Dimensions (L × W ×

Item Weight 0.731 lbs.

Mounting Style Surface / Wall Mount, Din-Rail Mount

 $7.78 \times 2.18 \times 1.22$ in.

Ports 10 USB Ports

Material of Construction Galvanized Steel

Country of Origin Taiwan
Compliance

H)

Certifications RoHS

UPC 045079163126

Series FFS-UH (Front-Facing Series Hubs)
Other Data

Weight 1.20625 lbs

Dimensions 9.583 × 6.605 × 2.448 in

Purchase order lets set you up.

Online with Credit card Orders shipped same day!

*orders placed prior to 3:30pm EST

1-888-688-2188 (Toll free)

sales@coolgear.com