

16 Port USB 3.2 Gen 1 Hub w/ ESD Surge Protection



Industrial Grade | +12~24V DC Input | Surge Protection | Surface Mountable | DIN Rail | Rack Mount | 5 Gbps | Screw Lock

Model No. USB3-16U1





- **Protect Your Equipment:** The 16-port USB 3.2 Gen 1 features 350 Watts of surge protection and 15kV ESD protection to keep your connected peripherals safe from
- Super Fast Speeds: This USB hub is 3.2 Gen 1 compliant, ensuring super-fast 5Gbps data transfer speeds. It supports super speed, high speed and full speed which enables it to be compatible with USB 2.0 / 1.1.
- Superior Build Quality: Housed in a rugged steel chassis with built in mountable flanges, the 16-port hub is perfect for installations in offices, labs, warehouses, heavy machinery, automation equipment, and other industrial applications.
- **Upstream:** 2 Selectable USB ports, Type B connector, Screw-lock type
- **Downstream:** 16 USB ports, Type A connectors, Screw-lock
- Power Connector: 2-Pin Terminal Block, DC Barrel
- LED Indicators: 16 LEDs for each downstream port to indicate the current bus power states
- Mounting Options: Wall, Surface, and DIN Rail
- Supply Current: 0.9A USB Bus Power for Each Downstream Port

Interested? LEARN MORE →

Questions? Speak to an engineering expert today!

Our on site engineers are ready to help you with your build.

1-727-209-1300 (Local) expert@coolgear.com



We Speak Your Speak - When you reach out to our support, you'll find yourself in the hands of a solutionoriented, knowledgeable expert ready to answer whatever question you throw at them. Go ahead, test us. We're Ready For Integration, Every Time. - Coolgear streamlines the task of selecting charging and connectivity products. For over 20 years our rugged, off-the-shelf USB hubs and serial products are ready to go for your next project.

Within every great machine, lives Coolgear. - At Coolgear, we're just as passionate about building

manufacturing methods, and conducts rigorous testing to ensure all our products are industrial-grade. This means greater duty cycle, zero data loss, and longer lasting builds. We promise.,	

PRODUCT SPECIFICATIONS

Looking for product documentation?

View CAD Models, Data sheet and Drawings here >



Operating Temperature 0°C to 55°C (32°F to 131°F)

Environmental Storage Temperature -20 to 75°C (-4 to 167°F)

Humidity 5% ~ 95% (non-condensing)

ESD Protection 15KV Surge Protection for Each Port

Isolated/Surge Protected Yes

Performance Max Data Transfer Rate 5Gbps

Over Voltage Protection Y per buck
Surge Protection 350W
Chipset GL 3522

Charging Protocols

Apple 2.4A, Charging Downstream Port (CDP), Dedicated

Charging Port (DCP)

Hardware LED Indicators Power

Overall Power Per USB

Port

5V per port

Per USB Port Current 0.9A

Product Information

USB

Other Data

Warranty 1 year from date of purchase

Input Voltage +12~24V DC

Over Voltage Protection Y per buck

Power Source

2-Pin Terminal Block, AC Adapter Not Included

Idle Consumption .70mA @ 24V Terminal Power, 13.98mA Bus Powered,

343.7mA @ 12V Terminal Power

External Power Required Yes

Software OS Support Win 11, Linux, Mac OSX, Win 10, Win 7, Win 8

What's in the Box Package Contents

2-Pin Terminal Block, DIN Rail Clip(s), Hub, Rack Mounting

Flanges, Screw Pack, USB-A to USB-B Cable

USB Type USB 3.0

Upstream USB Ports 2 Type-B Female USB **Downstream USB Ports** 16 Type-A Female USB

Isolated/Surge Protected Yes
Screw Lock Compatible Yes
Color Black

Item Dimensions (L × W ×

12.15 × 5.12 × 1.74 in.

Mechanical Item Weight 2.05 lbs.

H)

Mounting Style Surface / Wall Mount, Din-Rail Mount, Rack Mount

Ports 16 USB Ports

Material of Construction Galvanized Steel

UPC 729440692094

Series RMS-UH (Rack Mount Series Hubs)

Weight 3.75 lbs

Dimensions $14.5 \times 10.75 \times 4 \text{ in}$

Ready to Buy? Let's get to work!

Purchase order lets set you up.

Online with Credit card Orders shipped same day!

*orders placed prior to 3:30pm EST

1-888-688-2188 (Toll free)

sales@coolgear.com