



16 Port USB 3.2 Gen 1 Hub w/ ESD Surge Protection



Industrial Grade | +7~24V DC Input | Surface Mountable | DIN Rail | 5 Gbps | LED Indicators

Model No. CG-16PU31H



[View more
images here >](#)

- **Protect Your Equipment:** The 16-port USB 3.2 Gen 1 features 15kV ESD surge protection per port to keep your connected peripherals safe from harm.
- **Super Fast Speeds:** This USB hub is 3.2 Gen 1 compliant, ensuring super-fast 5Gbps data transfer speeds. It supports super speed, high speed and full speed which enables it to be compatible with USB 2.0 / 1.1.
- **Superior Build Quality:** Housed in a rugged steel chassis with built in mountable flanges, the 16-port hub is perfect for installations in offices, labs, warehouses, heavy machinery, automation equipment, and other industrial applications.
- **Upstream:** 1 USB port, Type B connector
- **Downstream:** 16 USB ports, Type A connectors
- **Power Connector:** 2-Pin Terminal Block
- **Mounting Options:** Wall, Surface, & DIN Rail
- **Supply Current:** 1.5A USB Power for Each Down-stream Port

Interested? LEARN MORE →

Questions? Speak to an engineering expert today!

Our on site engineers are ready to help you with your build.

☎ [1-727-209-1300](tel:1-727-209-1300) (Local) ✉ expert@coolgear.com



We Speak Your Speak - When you reach out to our support, you'll find yourself in the hands of a solution-oriented, knowledgeable expert ready to answer whatever question you throw at them. Go ahead, test us.

We're Ready For Integration, Every Time. - Coolgear streamlines the task of selecting charging and connectivity products. For over 20 years our rugged, off-the-shelf USB hubs and serial products are ready to go for your next project.

Within every great machine, lives Coolgear. - At Coolgear, we're just as passionate about building great products as you are. That's why we aim to meet or exceed your build specs every time.,

Advanced Engineering - Coolgear painstakingly sources high-quality components, oversees all manufacturing methods, and conducts rigorous testing to ensure all our products are industrial-grade. This means greater duty cycle, zero data loss, and longer lasting builds. We promise.,

PRODUCT SPECIFICATIONS

Looking for product documentation?

[View CAD Models, Data sheet and Drawings here >](#)




Environmental	Operating Temperature	0°C to 55°C (32°F to 131°F)
	Storage Temperature	-20 to 75°C (-4 to 167°F)
	Humidity	5% ~ 95% (non-condensing)
Performance	ESD Protection	15KV Surge Protection for Each Port
	Max Data Transfer Rate	5Gbps
	Over Current Protection	Y
	Over Voltage Protection	Y per buck
Hardware	Chipset	GL 3522
	Charging Protocols	Apple 2.4A, Charging Downstream Port (CDP), Dedicated Charging Port (DCP)
	LED Indicators	Power
	Per USB Port Current	1.5 A
Product Information	Warranty	1 year from date of purchase
	Input Voltage	+7~24V DC
	Over Current Protection	Y
Power	Over Voltage Protection	Y per buck
	Power Source	2-Pin Terminal Block, AC Adapter Not Included
	Idle Consumption	134mA @ 12V Terminal Power, 40.98mA Bus Powered
	External Power Required	No
Software	OS Support	Win 11, Linux, Mac OSX, Win 10, Win 7, Win 8
What's in the Box	Package Contents	2-Pin Terminal Block, DIN Rail Clip(s), Hub, Mounting Plate, Screw Pack, USB-A to USB-B Cable
USB	USB Type	USB 3.2 Gen 1
	Upstream USB Ports	1 Type-B Female USB
	Downstream USB Ports	16 Type-A Female USB
	Color	Black
Mechanical	Item Dimensions (L × W × H)	4.43 × 2.55 × 1.91 in.
	Item Weight	0.819 lbs.
	Mounting Style	Desktop, Surface / Wall Mount, Din-Rail Mount
	Ports	16 USB Ports
Compliance	Material of Construction	Galvanized Steel
	Country of Origin	Taiwan
	Certifications	REACH , RoHS
	Connector	2-Pin Terminal Block
Other Data	Series	DRS-UH (DIN-Rail Series Hubs)
	Weight	1.625 lbs
	Dimensions	11.562 × 7.375 × 2.625 in

Ready to Buy? Let's get to work!

Purchase order lets set you up.

Online with Credit card Orders shipped same day!

*orders placed prior to 3:30pm EST

 **1-888-688-2188 (Toll free)**

 **sales@coolgear.com**