

16 Port USB 3.2 Gen 1 Hub w/ ESD Surge Protection



Industrial Grade | +7~24V DC Input | Surface Mountable | DIN Rail | 5 Gbps | LED Indicators

Model No. CG-16PU31H





- **Protect Your Equipment:** The 16-port USB 3.2 Gen 1 features 15kV ESD surge protection per port to keep your connected peripherals safe from harm.
- Super Fast Speeds: This USB hub is 3.2 Gen 1 compliant, ensuring super-fast 5Gbps data transfer speeds. It supports super speed, high speed and full speed which enables it to be compatible with USB 2.0 / 1.1.
- Superior Build Quality: Housed in a rugged steel chassis with built in mountable flanges, the 16-port hub is perfect for installations in offices, labs, warehouses, heavy machinery, automation equipment, and other industrial applications.
- Upstream: 1 USB port, Type B connector
- **Downstream:** 16 USB ports, Type A connectors
- Power Connector: 2-Pin Terminal Block
- Mounting Options: Wall, Surface, & DIN Rail
- **Supply Current:** 1.5A USB Power for Each Down-stream Port

Interested? LEARN MORE →

Questions? Speak to an engineering expert today!

Our on site engineers are ready to help you with your build.

¹ 1-727-209-1300 (Local) **expert@coolgear.com**



We Speak Your Speak - When you reach out to our support, you'll find yourself in the hands of a solution-oriented, knowledgeable expert ready to answer whatever question you throw at them. Go ahead, test us.

We're Ready For Integration, Every Time. - Coolgear streamlines the task of selecting charging and connectivity products. For over 20 years our rugged, off-the-shelf USB hubs and serial products are ready to go for your next project.

Within every great machine, lives Coolgear. - At Coolgear, we're just as passionate about building great products as you are. That's why we aim to meet or exceed your build specs every time.,

Advanced Engineering - Coolgear painstakingly sources high-quality components, oversees all manufacturing methods, and conducts rigorous testing to ensure all our products are industrial-grade. This means greater duty cycle, zero data loss, and longer lasting builds. We promise.,

PRODUCT SPECIFICATIONS

Looking for product documentation?

View CAD Models, Data sheet and Drawings here >



Input Voltage +7~24V DC

Power Source 2-Pin Terminal Block, AC Adapter Not Included

Idle Consumption 134mA @ 12V Terminal Power, 40.98mA Bus Powered

Power External Power Required No

Charging Protocols

Apple 2.4A, Charging Downstream Port (CDP), Dedicated

Charging Port (DCP)

Per USB Port Current 1.5 A

Country of Origin Taiwan Compliance

Certifications REACH, RoHS, TAA

Color Black

Item Dimensions (L × W ×

4.43 × 2.55 × 1.91 in.

Characteristics Item Weight 0.819 lbs.

Mounting Style Desktop, Surface / Wall Mount, Din-Rail Mount

Ports 16 USB Ports

Material of Construction Galvanized Steel

What's in the Box Package Contents

2-Pin Terminal Block, DIN Rail Clip(s), Hub, Mounting Plate,

Screw Pack, USB-A to USB-B Cable

Software OS Support Win 7, Win 8, Win 10, Win 11, Linux, Mac OSX

Operating Temperature 0°C to 55°C (32°F to 131°F)

Environmental Storage Temperature -20 to 75°C (-4 to 167°F)

Humidity 5% ~ 95% (non-condensing)

Product

Physical

Warranty 1 year from date of purchase

Chipset GL 3522

LED Indicators Power Hardware

Downstream USB Ports 16 Type-A Female USB **Upstream USB Ports** 1 Type-B Female USB

ESD Protection 15KV Surge Protection for Each Port

Performance & Max Data Transfer Rate 5Gbps

Safety Over Current Protection Yes

Over Voltage Protection Yes per buck
USB Interface USB 3.2 Gen 1

Connector 2-Pin Terminal Block

Other Data Series DRS-UH (DIN-Rail Series Hubs)

Weight 1.625 lbs

Dimensions 11.562 × 7.375 × 2.625 in

Ready to Buy? Let's get to work!

Purchase order lets set you up.

1-888-688-2188 (Toll free)

Online with Credit card Orders shipped same day!

*orders placed prior to 3:30pm EST

Sales@coolgear.com