



2-Port RS-232 / RS-422 / RS-485 Serial to Ethernet Device Server, PoE Powered w/Terminal Block Interface



Model No. MSD-SRP2XM-TBPRO

The **MSD-SRP2XM-TBPRO** is a multi-protocol RS-232 and RS-422 / 485 serial device server that is designed to connect RS-232, RS-422 and RS-485 serial devices including POS, barcode readers, sensors, meters, weighing systems, CNC controllers and PLC to an IP-based Ethernet Network. The **MSD-SRP2XM-TBPRO** provides 2 ports, port 1 supports RS-232 mode only and port 2 supports RS-422 / 485 modes.

Interested? [LEARN MORE →](#)



Questions? Speak to an engineering expert today!

Our on site engineers are ready to help you with your build.

☎ **1-727-209-1300** (Local) ✉ **expert@coolgear.com**



We Speak Your Speak - When you reach out to our support, you'll find yourself in the hands of a solution-oriented, knowledgeable expert ready to answer whatever question you throw at them. Go ahead, test us.

We're Ready For Integration, Every Time. - Coolgear streamlines the task of selecting charging and connectivity products. For over 20 years our rugged, off-the-shelf USB hubs and serial products are ready to go for your next project.

Within every great machine, lives Coolgear. - At Coolgear, we're just as passionate about building great products as you are. That's why we aim to meet or exceed your build specs every time.,

Advanced Engineering - Coolgear painstakingly sources high-quality components, oversees all manufacturing methods, and conducts rigorous testing to ensure all our products are industrial-grade. This

means greater duty cycle, zero data loss, and longer lasting builds. We promise.,
Coolgear | Charging & Connectivity Experts Visit coolgear.com/support for any questions & inquiries.
www.coolgear.com

PRODUCT SPECIFICATIONS

Looking for product documentation?

[View CAD Models, Data sheet and Drawings here >](#)



Environmental	Operating Temperature	0 to 60C
	Storage Temperature	-20°C to 75°C
	Humidity	5% ~ 95% (non-condensing)
Performance	ESD Protection	15KV Surge Protection for Each Port
Power	Input Voltage	+5V DC
Software	OS Support	Win 10, Win 7, Win 8, Win 8.1, Win Vista, Win XP
Serial Attributes	Serial Standards	RS232/RS422/RS485
	Baud Rate	921.6K bps
	Serial Ports	2
Mechanical	Item Dimensions (L × W × H)	3.22 × 1.81 × 0.99 in.
	Item Weight	0.34 lbs.
Compliance	Compliance	IEEE 802.3, IEEE 802.3u
Other Data	UPC	045079163287
	Connector	DC Barrel, RJ45
	Weight	1.10625 lbs
	Dimensions	9.54 × 6.65 × 2.23 in

Ready to Buy? Let's get to work!

[Purchase order](#) lets set you up.

[Online with Credit card](#) Orders shipped same day!

*orders placed prior to 3:30pm EST

☎ [1-888-688-2188 \(Toll free\)](tel:1-888-688-2188)

✉ sales@coolgear.com