



2-Port USB to Serial Adapter (RS-232/422/485), DIN-rail



Model No. USB-2COMi-PRO



- Adds two RS-232, RS-422, or RS-485 serial ports via USB connection.
- Software configuration for easy RS-232, RS-422, RS-485 mode settings.
- *Remote Serial Port Sharing*: allows remote access to USB serial port regardless of its physical location.
- Software configuration of serial port type, operation modes, termination resistors and Biasing.
- 512 byte transmit buffer and 512 byte receive buffer using buffer smoothing technology for high data throughput.
- ESD surge protection of 15 KV.
- Monitor LEDs of Power, TxD, RxD indicating power & port status.

Interested? [LEARN MORE →](#)



[View more images here >](#)

Questions? Speak to an engineering expert today!

Our on site engineers are ready to help you with your build.

☎ [1-727-209-1300](tel:1-727-209-1300) (Local) ✉ expert@coolgear.com



We Speak Your Speak - When you reach out to our support, you'll find yourself in the hands of a solution-oriented, knowledgeable expert ready to answer whatever question you throw at them. Go ahead, test us.

We're Ready For Integration, Every Time. - Coolgear streamlines the task of selecting charging and connectivity products. For over 20 years our rugged, off-the-shelf USB hubs and serial products are ready to go for your next project.

Within every great machine, lives Coolgear. - At Coolgear, we're just as passionate about building great products as you are. That's why we aim to meet or exceed your build specs every time.,

Advanced Engineering - Coolgear painstakingly sources high-quality components, oversees all manufacturing methods, and conducts rigorous testing to ensure all our products are industrial-grade. This means greater duty cycle, zero data loss, and longer lasting builds. We promise.,

PRODUCT SPECIFICATIONS

Looking for product documentation?
[View CAD Models, Data sheet and Drawings here >](#)



Serial Attributes	Performance	ESD Protection	15KV Surge Protection for Each Port
	Hardware	LED Indicators	?
	Software	OS Support	Windows 10, 8, Windows 7, Windows Vista 32-bit, Vista 64-bit, Windows Server 2016, 2012, 2008, 2003, XP; Linux 3.2 and greater; Mac OS-X
	USB	Serial Standards	RS232/RS422/RS485
		Serial Ports	2
		Upstream USB Ports	1 Type-B Female USB
	Mechanical	Supported Data Speed	300bps to 3Mbps
		Item Dimensions (L × W × H)	57mm x 76mm x 23mm (with DIN rail bracket)
		Item Weight	10.2 oz.
	Other Data	Mounting Style	Surface Mount (Optional Brackets)
		UPC	045079162914
		Weight	0.99375 lbs
	Dimensions	6.40 × 4.76 × 2.12 in	

Ready to Buy? Let's get to work!

Purchase order lets set you up.

Online with Credit card Orders shipped same day!

*orders placed prior to 3:30pm EST

☎ [1-888-688-2188](tel:1-888-688-2188) (Toll free)

✉ sales@coolgear.com