

32 Port RS-232 USB-to-Serial Adapter



Serial USB Adapter - Full RS232 Modem Control

Model No. USB-32COM-RM



The USB-32COM-RM USB to 32 Port RS-232 Serial Adapter is designed for industrial applications and harsh environments making serial port connections easier. The USB-32COM-RM is a rack mountable industrial USB to 32 Port RS-232 Serial adapter that allows you to add thirty two RS-232 serial ports by connecting to a single USB host port.

- Adds 32 RS232 Serial Ports through Plug and Play installation with no conflicts.
- Works in Self-Powered mode with a built-in switching power supply of 100V/240V input.
- Manufactured for industrial environments, the adapter is DIN-Rail Mountable.
- Features full RS-232 modem control signals and hardware/software flow control with RS-232 data signals TxD, RxD, RTS, CTS, DSR, DTR, DCD, GND



Interested? LEARN MORE →

Questions? Speak to an engineering expert today!

Our on site engineers are ready to help you with your build.

¹ 1-727-209-1300 (Local) **expert@coolgear.com**



We Speak Your Speak - When you reach out to our support, you'll find yourself in the hands of a solution-oriented, knowledgeable expert ready to answer whatever question you throw at them. Go ahead, test us.

We're Ready For Integration, Every Time. - Coolgear streamlines the task of selecting charging and connectivity products. For over 20 years our rugged, off-the-shelf USB hubs and serial products are ready to go for your next project.

Within every great machine, lives Coolgear. - At Coolgear, we're just as passionate about building great products as you are. That's why we aim to meet or exceed your build specs every time.,

Advanced Engineering - Coolgear painstakingly sources high-quality components, oversees all manufacturing methods, and conducts rigorous testing to ensure all our products are industrial-grade. This means greater duty cycle, zero data loss, and longer lasting builds. We promise.,

PRODUCT SPECIFICATIONS

Looking for product documentation?

View CAD Models, Data sheet and Drawings here >



Environmental Operating Temperature 0C to 55C

Hardware Chipset FTDI

Software OS Support Linux, Mac OSX, Win 10, Win 7, Win 8, Win XP

Serial Attributes Serial Standards RS232

H)

Color Black

Item Dimensions (L × W ×

16.89 × 5.79 × 1.73 in.

Mechanical Length 5ft

Mounting Style Rack Mount, Surface Mount

Ports 32 Serial Ports

Country of Origin Taiwan

Compliance RoHS, TAA

Connector RJ45

Chip Model FT4232HL, GL852GT, ZT3243LFEA

Other Data Warranty 1 year from date of purchase

Weight 13 lbs

Dimensions 22.5 × 8.5 × 5.25 in

Ready to Buy? Let's get to work!

Purchase order lets set you up.

Online with Credit card Orders shipped same day!

*orders placed prior to 3:30pm EST

1-888-688-2188 (Toll free)

sales@coolgear.com