

36in. USB to DB-9 Serial RS-232 High Speed Adapter w/ FTDI Chipset



Model No. USBG-RS232-F36





RS-232 | FTDI

- Expand Your Serial Capabilities: Connect your legacy 9-pin serial device through a USB-A port to add legacy functionality to newer technologies with no serial port connections.
- Safe Connections: Designed with a unique system load reduction feature, the Mini USB to Serial Adapter also offers 10kV surge protection for connected devices.
- Plug-&-Play: The adapter's power is drawn from a USB connection for ease of access and is compatible with Windows (up to Win 11), Mac OS, and Linux.
- **COM Retention:** COM Ports are fully configurable, and after reboots, port assignments are preserved.
- Upstream: 1 USB port, Type A Male Connector
- Downstream: 1 Male DB9, w/ nuts
- LEDs: Power, TX / RX

Interested? LEARN MORE >

Questions? Speak to an engineering expert today!

Our on site engineers are ready to help you with your build.

¹ 1-727-209-1300 (Local) **expert@coolgear.com**



We Speak Your Speak - When you reach out to our support, you'll find yourself in the hands of a solution-oriented, knowledgeable expert ready to answer whatever question you throw at them. Go ahead, test us.

We're Ready For Integration, Every Time. - Coolgear streamlines the task of selecting charging and connectivity products. For over 20 years our rugged, off-the-shelf USB hubs and serial products are ready to go for your next project.

Within every great machine, lives Coolgear. - At Coolgear, we're just as passionate about building great products as you are. That's why we aim to meet or exceed your build specs every time.,

Advanced Engineering - Coolgear painstakingly sources high-quality components, oversees all manufacturing methods, and conducts rigorous testing to ensure all our products are industrial-grade. This means greater duty cycle, zero data loss, and longer lasting builds. We promise.,

PRODUCT SPECIFICATIONS

Looking for product documentation?

View CAD Models, Data sheet and Drawings here >



Chipset FTDI Hardware

LED Indicators Power, TX / RX

Product Information Warranty 1 year from date of purchase

Power External Power Required No

Software OS Support Win 11, Linux, Mac OSX, Win 10, Win 7, Win 8

RS Signals TxD, RxD, RTS, CTS, DSR, DTR, DCD, RI, GND

Serial Standards RS232
Baud Rate 921.6K bps

Serial Attributes Data Bits 7,8

Parity None, Even, Odd, Mark, Space

Stop Bits 1, 2

Flow Control Hardware (RTS, CTS), XON/XOFF

USB Type USB 2.0

Screw Lock Compatible Yes

Color Black Length 3ft

Ports 1 Serial Port

Material of Construction Plastic

Compliance Country of Origin Taiwan

Connector DB9 Male w/ Nuts

Chip Model FT232BL
Other Data

Weight .3 lbs

Dimensions $7 \times 4 \times 1.5 \text{ in}$

Ready to Buy? Let's get to work!

Purchase order lets set you up.

Online with Credit card Orders shipped same day!

*orders placed prior to 3:30pm EST

Mechanical

1-888-688-2188 (Toll free)

sales@coolgear.com