# coolgear 36in. USB to DB-9 Serial RS-232 High Speed Adapter w/ FTDI Chipset



Model No. USBG-RS232-F36



## RS-232 | FTDI

- Expand Your Serial Capabilities: Connect your legacy 9-pin serial device through a USB-A port to add legacy functionality to newer technologies with no serial port connections.
- Safe Connections: Designed with a unique system load reduction feature, the Mini USB to Serial Adapter also offers 10kV surge protection for connected devices.
- **Plug-&-Play:** The adapter's power is drawn from a USB connection for ease of access and is compatible with Windows (up to Win 11), Mac OS, and Linux.
- **COM Retention:** COM Ports are fully configurable, and after reboots, port assignments are preserved.
- Upstream: 1 USB port, Type A Male Connector
- Downstream: 1 Male DB9, w/ nuts
- LEDs: Power, TX / RX

#### Interested? LEARN MORE →

# **Questions?** Speak to an engineering expert today!

Our on site engineers are ready to help you with your build.

<sup>ℓ</sup> 1-727-209-1300 (Local) <sup>IIII</sup> expert@coolgear.com



We Speak Your Speak - When you reach out to our support, you'll find yourself in the hands of a solutionoriented, knowledgeable expert ready to answer whatever question you throw at them. Go ahead, test us. We're Ready For Integration, Every Time. - Coolgear streamlines the task of selecting charging and connectivity products. For over 20 years our rugged, off-the-shelf USB hubs and serial products are ready to go for your next project.

Within every great machine, lives Coolgear. - At Coolgear, we're just as passionate about building great products as you are. That's why we aim to meet or exceed your build specs every time.,

**Advanced Engineering** - Coolgear painstakingly sources high-quality components, oversees all manufacturing methods, and conducts rigorous testing to ensure all our products are industrial-grade. This means greater duty cycle, zero data loss, and longer lasting builds. We promise.,



# PRODUCT SPECIFICATIONS

Hardware	Chipset	FTDI
	LED Indicators	Power, TX / RX
<b>Product Information</b>	Warranty	1 year from date of purchase
Power	<b>External Power Required</b>	No
Software	OS Support	Win 11, Linux, Mac OSX, Win 10, Win 7, Win 8
	RS Signals	TxD, RxD, RTS, CTS, DSR, DTR, DCD, RI, GND
Serial Attributes	Serial Standards	RS232
	Baud Rate	921.6K bps
	Data Bits	7,8
	Parity	None, Even, Odd, Mark, Space
	Stop Bits	1, 2
	Flow Control	Hardware (RTS, CTS), XON/XOFF
USB	USB Type	USB 2.0
	Screw Lock Compatible	Yes
	Color	Black
Mechanical	Length	3ft
	Ports	1 Serial Port
	Material of Construction	Plastic
Compliance	Country of Origin	Taiwan
Other Data	Connector	DB9 Male w/ Nuts
	Chip Model	FT232BL
	Weight	.3 lbs
	Dimensions	7 × 4 × 1.5 in

## Ready to Buy? Let's get to work!

Purchase orderlets set you up.Online with Credit cardOrders shipped same day!

\*orders placed prior to 3:30pm EST

- <sup>(</sup> <u>1-888-688-2188 (Toll free)</u>
- sales@coolgear.com