



4-Port RS-232 USB to Serial Adapter Data Control Box



Model No. USB-4COM



[View more images here >](#)

RS-232 | 128 Bytes Receive | 384 Bytes Transmit | FTDI

- **Expand Your Serial Capabilities:** Connect 4 legacy 9-pin serial devices through a USB-A port to add legacy functionality to newer technologies with no serial port connections.
- **Safe Connections:** Designed with a unique system load reduction feature, the Mini USB to Serial Adapter also offers 15kV surge protection for connected devices.
- **Plug-&-Play:** The adapter's power is drawn from a USB connection for ease of access and is compatible with Windows (up to Win 11), Mac OS, and Linux.
- **COM Retention:** COM Ports are fully configurable, and after reboots, port assignments are preserved.
- **Upstream:** 1 USB port, Type B Female Connector
- **Downstream:** 4 Male DB9, w/ nuts
- **LEDs:** Power, TX / RX

Interested? LEARN MORE →

Questions? Speak to an engineering expert today!

Our on site engineers are ready to help you with your build.

☎ **1-727-209-1300** (Local) ✉ **expert@coolgear.com**



We Speak Your Speak - When you reach out to our support, you'll find yourself in the hands of a solution-oriented, knowledgeable expert ready to answer whatever question you throw at them. Go ahead, test us.

We're Ready For Integration, Every Time. - Coolgear streamlines the task of selecting charging and connectivity products. For over 20 years our rugged, off-the-shelf USB hubs and serial products are ready to go for your next project.

Within every great machine, lives Coolgear. - At Coolgear, we're just as passionate about building great products as you are. That's why we aim to meet or exceed your build specs every time.,

Advanced Engineering - Coolgear painstakingly sources high-quality components, oversees all manufacturing methods, and conducts rigorous testing to ensure all our products are industrial-grade. This means greater duty cycle, zero data loss, and longer lasting builds. We promise.,

PRODUCT SPECIFICATIONS

Looking for product documentation?

[View CAD Models, Data sheet and Drawings here >](#)



Environmental	Operating Temperature	0°C to 55°C (32°F to 131°F)	
	Storage Temperature	-20 to 75°C (-4 to 167°F)	
	Humidity	5% ~ 95% (non-condensing)	
Hardware	Chipset	FTDI	
	LED Indicators	Power, TX / RX	
Product Information	Warranty	1 year from date of purchase	
Power	External Power Required	No	
Serial Attributes	Software	OS Support	Win 11, Linux, Mac OSX, Win 10, Win 7, Win 8
		RS Signals	DCD, RxD, TxD, DTR, GND, DSR, RTS, CTS, RI
		Serial Standards	RS232
		Baud Rate	921.6K bps
		FIFO Receive	384 bytes
		FIFO Transmit	128 bytes
		Data Bits	5, 6, 7, 8
		Parity	None, Even, Odd, Mark, Space
		Stop Bits	1, 1.5, 2
		Flow Control	Hardware (RTS, CTS), XON/XOFF
	USB	USB Type	USB 2.0
		Upstream USB Ports	1 Micro Type-B Female USB
		Screw Lock Compatible	Yes
Color		Silver	
Mechanical	Item Dimensions (L × W × H)	5.43 × 5.10 × 1.56 in.	
	Mounting Style	Desktop, Surface Mount	
	Ports	4 Serial Ports	
	Material of Construction	Plastic	
Compliance	Country of Origin	Taiwan	
	Compliance	TAA	
Other Data	Connector	DB9 Male w/ Nuts	
	Chip Model	FT4232HL, SP3243EUEA	
	Weight	.8 lbs	
	Dimensions	6 × 6 × 2.5 in	

Ready to Buy? Let's get to work!

Purchase order lets set you up.

Online with Credit card Orders shipped same day!

*orders placed prior to 3:30pm EST

 **1-888-688-2188 (Toll free)**

 **sales@coolgear.com**