



4-Port RS-422 / 485 USB to Serial Adapter



RS485 to USB Adapter Auto Transmit

Model No. USB-4COMi-M



A 4-Port RS-422, RS-485 adapter for serial communication that utilizes four external DIP switches for easy access to the signal used. Automatic transmit and receive control for 2-wire RS-485 half-duplex mode.

- Use your existing USB port to expand your serial communication.
- Self-powered, with one switching power adapter 5V 2A included.
- High-Speed Communication with 128 byte FIFO chip, works through heavy loads.
- Industrial-grade metal housing for rugged applications.

Interested? [LEARN MORE →](#)



[View more images here >](#)

Questions? Speak to an engineering expert today!

Our on site engineers are ready to help you with your build.

☎ [1-727-209-1300](tel:1-727-209-1300) (Local) ✉ expert@coolgear.com



We Speak Your Speak - When you reach out to our support, you'll find yourself in the hands of a solution-oriented, knowledgeable expert ready to answer whatever question you throw at them. Go ahead, test us.

We're Ready For Integration, Every Time. - Coolgear streamlines the task of selecting charging and connectivity products. For over 20 years our rugged, off-the-shelf USB hubs and serial products are ready to go for your next project.

Within every great machine, lives Coolgear. - At Coolgear, we're just as passionate about building great products as you are. That's why we aim to meet or exceed your build specs every time.,

Advanced Engineering - Coolgear painstakingly sources high-quality components, oversees all manufacturing methods, and conducts rigorous testing to ensure all our products are industrial-grade. This means greater duty cycle, zero data loss, and longer lasting builds. We promise.,

PRODUCT SPECIFICATIONS

Looking for product documentation?
[View CAD Models, Data sheet and Drawings here >](#)



Environmental	Operating Temperature	0C to 55C
Hardware	Chipset	FTDI
Power	Input Voltage	+5V DC
Software	OS Support	Linux, Mac OSX, Win 10, Win 7, Win 8
Serial Attributes	Serial Standards	RS422, RS485
	Color	Black
Mechanical	Mounting Style	Surface Mount
	Ports	4 Serial Ports
	Country of Origin	Taiwan
Compliance	Certifications	CE , FCC
	Compliance	RoHS, TAA
	Connector	DB9 Male w/ Nuts
	Chip Model	FT4232HL, MAX3089E
Other Data	Warranty	1 year from date of purchase
	Weight	2.2 lbs
	Dimensions	13.25 × 7.25 × 2.75 in

Ready to Buy? Let's get to work!

[Purchase order](#) lets set you up.

[Online with Credit card](#) Orders shipped same day!

*orders placed prior to 3:30pm EST

 [1-888-688-2188](tel:1-888-688-2188) (Toll free)

 sales@coolgear.com