

4 Port USB 3.2 Gen 2 Type-C Hub w/ Screw-Locking Ports & Status LEDs



Industrial Grade | +7~24V DC Input | DIN Rail | 10 Gbps | Screw Lock

Model No. CG-4P31CHUB





- Super Fast Speeds: This USB hub is 3.2 Gen 2 compliant, ensuring super-fast 10Gbps data transfer speeds. It supports super speed +, high speed and full speed which enables it to be compatible with USB 3.2 Gen 1 / 2.0 / 1.1.
- Secure Connections: Each port features a screw locking for safe and secure USB connections.
- Check Your Ports' Status: Quickly check the status of each port individually with built in LED indicators.
- Upstream: 1 USB port, Type C connector, Screw-lock type
- **Downstream:** 2 USB ports, Type C connectors, Screw-lock type & 2 USB ports, Type A connectors, Screw-lock type
- Power Connector: 2-Pin Terminal Block, DC Barrel 2.1mm
 ID × 5.5mm OD
- LED Indicators: 4 LEDs for each downstream port to indicate the current bus
- Mounting Options: Desktop, Wall, Surface & DIN Rail

Interested? LEARN MORE >

Questions? Speak to an engineering expert today!

Our on site engineers are ready to help you with your build.

¹ 1-727-209-1300 (Local) **expert@coolgear.com**



We Speak Your Speak - When you reach out to our support, you'll find yourself in the hands of a solution-oriented, knowledgeable expert ready to answer whatever question you throw at them. Go ahead, test us.

We're Ready For Integration, Every Time. - Coolgear streamlines the task of selecting charging and connectivity products. For over 20 years our rugged, off-the-shelf USB hubs and serial products are ready to go for your next project.

Within every great machine, lives Coolgear. - At Coolgear, we're just as passionate about building great products as you are. That's why we aim to meet or exceed your build specs every time.,

Advanced Engineering - Coolgear painstakingly sources high-quality components, oversees all manufacturing methods, and conducts rigorous testing to ensure all our products are industrial-grade. This means greater duty cycle, zero data loss, and longer lasting builds. We promise.,

PRODUCT SPECIFICATIONS

Looking for product documentation?

View CAD Models, Data sheet and Drawings here >



Operating Temperature 0°C to 70°C (32°F to 158°F)

Environmental Storage Temperature -20°C to 85°C (-4°F to 185°F)

Humidity 5% ~ 95% (non-condensing)

Max Data Transfer Rate 10Gbps

Performance Over Current Protection Y

Over Voltage Protection Y

Chipset VL820-Q8

Cinpset VE020 QC

Charging Protocols

Hardware

BC 1.2, Charging Downstream Port (CDP), Dedicated
Charging Port (DCP), Standard Downstream Port (SDP)

LED Indicators Port Status, Power

Per USB Port Current 1.5 Amp

Product Information

Warranty 1 year from date of purchase

Input Voltage +7~24V DC

Over Current Protection Y
Over Voltage Protection Y

2-Pin Terminal Block, AC Adapter Included, DC Barrel Jack

2.1mm ID x 5.5mm OD

Power Idle Consumption 61.16mA Bus Powered

Adapter Input Current 1A

Adapter Input Voltage 100~240V AC

Adapter Output Current 3A
Adapter Output Voltage 12V DC
External Power Required No

Software OS Support Win 11, Linux, Mac OSX, Win 10, Win 7, Win 8

What's in the Box Package Contents

Hub, Mounting Plate, Power Adapter, USB-C to Screw Lock

USB-C Cable

USB Type USB 3.2 Gen 2

Upstream USB Ports 1 USB Type-C Female USB USB

Downstream USB Ports 2 Type-A Female USB, 2 Type-C Female USB

Screw Lock Compatible Y

Color White

Item Dimensions (L × W × 152.04 x 62.45 x 30mm (LxWxH)

H) Item Weight .34 lbs.

Mounting Style Surface / Wall Mount, Din-Rail Mount

Ports 4 USB Ports

Material of Construction Plastic

Country of Origin Taiwan
Compliance

Certifications <u>CE</u>

Mechanical

UPC 045079162853

Other Data

Series

DTS-UH (Desktop Series Hubs)

Weight 0.800 lbs

Dimensions 9.500 × 6.500 × 2.125 in

Ready to Buy? Let's get to work!

Purchase order lets set you up.

Online with Credit card Orders shipped same day!

*orders placed prior to 3:30pm EST

1-888-688-2188 (Toll free)

sales@coolgear.com