

4 Port USB 3.2 Gen 1 Type-C Hub w/ ESD Surge Protection & Screw Locking Ports



Industrial Grade | +7~48V DC Input | Surge Protection | Surface Mountable | DIN Rail | 5 Gbps | Screw Lock

Model No. CG-4U3CML





- Protect Your Equipment: The 4-port Type-C hub supports 15KV ESD surge protection for each port to keep your connected peripherals safe from harm.
- Super Fast Speeds: This USB hub is 3.2 Gen 1 compliant, ensuring super-fast 5Gbps data transfer speeds. It supports super speed, high speed and full speed which enables it to be compatible with USB 2.0 / 1.1.
- Superior Build Quality: Housed in a rugged steel chassis with built in mountable flanges, the 4-port hub is perfect for workstations installations in offices, labs, warehouses, and other industrial applications.
- Upstream: 1 USB-C port, Screw-lock type
- Downstream: 4 USB-C port, Screw-lock type
- Power Connector: 2-Pin Terminal Block, DC Barrel Jack 2.1mm ID × 5.5mm OD
- Mounting Options: Wall & Surface
- Supply Current: 900mA USB Bus Power for Each Downstream Port

Interested? LEARN MORE →

Questions? Speak to an engineering expert today!

Our on site engineers are ready to help you with your build.

1-727-209-1300 (Local) expert@coolgear.com



We Speak Your Speak - When you reach out to our support, you'll find yourself in the hands of a solution-oriented, knowledgeable expert ready to answer whatever question you throw at them. Go ahead, test us.

We're Ready For Integration, Every Time. - Coolgear streamlines the task of selecting charging and connectivity products. For over 20 years our rugged, off-the-shelf USB hubs and serial products are ready to go for your next project.

Within every great machine, lives Coolgear. - At Coolgear, we're just as passionate about building great products as you are. That's why we aim to meet or exceed your build specs every time.,

Advanced Engineering - Coolgear painstakingly sources high-quality components, oversees all manufacturing methods, and conducts rigorous testing to ensure all our products are industrial-grade. This means greater duty cycle, zero data loss, and longer lasting builds. We promise.,

PRODUCT SPECIFICATIONS

Looking for product documentation?

View CAD Models, Data sheet and Drawings here >



Operating Temperature 0°C to 55°C (32°F to 131°F)

Environmental Storage Temperature -20 to 75°C (-4 to 167°F)

Humidity 5% ~ 95% (non-condensing)

ESD Protection 15KV Surge Protection for Each Port

Isolated/Surge Protected Yes
Performance

Max Data Transfer Rate 5Gbps

Over Current Protection Y

Chipset GL 3523

Charging Protocols

Charging Protocols

Charging Downstream Port (CDP), Dedicated Charging Port

(DCP) **LED Indicators**Power

Per USB Port Current 2.4 Amp max per port, 0.9 Amp for all ports simultaneously

Product

Hardware

Warranty 1 year from date of purchase

Input Voltage +7~48V DC

Over Current Protection Y

Power Source 2-Pin Terminal Block, AC Adapter Not Included, DC Barrel

Jack 2.1mm ID x 5.5mm OD

Idle Consumption 54.30mA - Bus Powered, 55mA @ 12V Terminal Power

External Power Required No

Software OS Support Win 11, Linux, Mac OSX, Win 10, Win 7, Win 8

What's in the Box Package Contents

2-Pin Terminal Block, DIN Rail Clip(s), Hub, Screw Pack, USB-

C to Screw Lock USB-C Cable

USB Type USB 3.2 Gen 1

Upstream USB Ports 1 Type-C Female USB

USB Downstream USB Ports 4 Type-C Female USB

Isolated/Surge Protected Yes
Screw Lock Compatible Yes
Color Black

Item Dimensions (L × W ×

H)

6.5 x 2.25 x 1.25 in.

Mechanical Item Weight 9.5 oz

Mounting Style Surface / Wall Mount, Din-Rail Mount

Ports 4 USB Ports

Material of Construction Galvanized Steel

Country of Origin Taiwan Compliance

Certifications REACH, RoHS
UPC 045079162488

Series FFS-UH (Front-Facing Series Hubs)
Other Data

Weight 1.375 lbs

Dimensions 9.75 × 6.75 × 2.25 in

Ready to Buy? Let's get to work!

Purchase order lets set you up.

Online with Credit card Orders shipped same day!

*orders placed prior to 3:30pm EST

1-888-688-2188 (Toll free)

sales@coolgear.com