




4 Port USB 3.2 Gen 1 Hub PCBA w/ ESD Surge Protection & Port Status LEDs



+7~48V DC Input | 5 Gbps | LED Indicators

Model No. USBG-3X4MR2-
PCBA



- **Protect Your Equipment:** The 4-port USB 3.2 Gen 1 features 15kV ESD surge protection per port to keep your connected peripherals safe from harm.
- **Super Fast Speeds:** This USB hub is 3.2 Gen 1 compliant, ensuring super-fast 5Gbps data transfer speeds. It supports super speed, high speed and full speed which enables it to be compatible with USB 2.0 / 1.1.
- **Check Your Ports' Status:** Quickly check the status of each port individually with built in LED indicators.
- **Upstream:** 1 USB port, Type B connector
- **Downstream:** 4 USB ports, Type A connectors
- **Power Connector:** 2-Pin Terminal Block, DC Barrel 2.1mm ID x 5.5mm OD
- **Supply Current:** 900mA USB Bus Power for Each Downstream Port

Interested? [LEARN MORE →](#)



Questions? Speak to an engineering expert today!

Our on site engineers are ready to help you with your build.

☎ [1-727-209-1300](tel:1-727-209-1300) (Local) ✉ expert@coolgear.com



We Speak Your Speak - When you reach out to our support, you'll find yourself in the hands of a solution-oriented, knowledgeable expert ready to answer whatever question you throw at them. Go ahead, test us.

We're Ready For Integration, Every Time. - Coolgear streamlines the task of selecting charging and connectivity products. For over 20 years our rugged, off-the-shelf USB hubs and serial products are ready to go for your next project.

Within every great machine, lives Coolgear. - At Coolgear, we're just as passionate about building great products as you are. That's why we aim to meet or exceed your build specs every time.,

Advanced Engineering - Coolgear painstakingly sources high-quality components, oversees all manufacturing methods, and conducts rigorous testing to ensure all our products are industrial-grade. This means greater duty cycle, zero data loss, and longer lasting builds. We promise.,

PRODUCT SPECIFICATIONS

Looking for product documentation?

[View CAD Models, Data sheet and Drawings here >](#)



| | | |
|---------------------|------------------------------------|--|
| Environmental | Operating Temperature | 0°C to 55°C (32°F to 131°F) |
| | Storage Temperature | -20 to 75°C (-4 to 167°F) |
| | Humidity | 5% ~ 95% (non-condensing) |
| | ESD Protection | 15KV Surge Protection for Each Port |
| Performance | Isolated/Surge Protected | Yes |
| | Max Data Transfer Rate | 5Gbps |
| | Over Current Protection | Y |
| | Chipset | GL 3520 |
| Hardware | Charging Protocols | Apple 2.4A, Charging Downstream Port (CDP), Dedicated Charging Port (DCP), Samsung, Standard Downstream Port (SDP) |
| | LED Indicators | Port Status, Power |
| | Per USB Port Current | 900mA maximum |
| | Warranty | 1 year from date of purchase |
| Product Information | Input Voltage | +7~48V DC |
| | Over Current Protection | Y |
| | Power Source | 2-Pin Terminal Block, AC Adapter Not Included, DC Barrel Jack 2.1mm ID x 5.5mm OD |
| | Idle Consumption | 0.47mA – 12V Terminal Power, 28.43mA – Bus Powered |
| Power | External Power Required | No |
| | OS Support | Win 11, Linux, Mac OSX, Win 10, Win 7, Win 8 |
| | USB Type | USB 3.2 Gen 1 |
| | Upstream USB Ports | 1 USB-B Port |
| USB | Downstream USB Ports | 4 Type-A Female USB |
| | Isolated/Surge Protected | Yes |
| | Item Dimensions (L x W x H) | 5.55 x 2.24 x 0.70 in. |
| | Item Weight | 0.12 lbs. |
| Mechanical | Ports | 4 USB Ports |
| | Country of Origin | Taiwan |
| | Certifications | REACH , TAA Hubs , CE , FCC , RoHS |
| | UPC | 045079163522 |
| Other Data | Weight | 0.1375 lbs |
| | Dimensions | 7 x 4.75 x 0.8 in |

Ready to Buy? Let's get to work!

Purchase order lets set you up.

Online with Credit card Orders shipped same day!

1-888-688-2188 (Toll free)

*orders placed prior to 3:30pm EST

 sales@coolgear.com