

4 Port USB 3.1 Gen1 Isolated Hub with 15KV ESD Surge Protection



Isolated Downstream Hub Ports

Model No. CG-U31iS4PH



The new USB 3.14 port hub isolates the four downstream ports from the upstream host port giving you valued circuit protection. With a small footprint, the hub supports 5Gbps super-speed data and backwards compatibility down to USB 1.0 1.5Mbps. With its DIN RAIL mounting plate, it's an ideal hub mountable hub with protection

- Compliant with USb 3.1 Gen1 Specifications
- Up to 3KV AC Isolation Between Upstream and Downstream Ports
- Supports up to 15KV ESD Surge Protection for Each Port
- Supports USB Battery Charging BC 1.2 CDP and DCP modes
- Supports DIN RAIL Mounting Option and Wall Mounting Bracket

Interested? LEARN MORE >



Questions? Speak to an engineering expert today!

Our on site engineers are ready to help you with your build.

¹ 1-727-209-1300 (Local) **expert@coolgear.com**



We Speak Your Speak - When you reach out to our support, you'll find yourself in the hands of a solution-oriented, knowledgeable expert ready to answer whatever question you throw at them. Go ahead, test us.

We're Ready For Integration, Every Time. - Coolgear streamlines the task of selecting charging and connectivity products. For over 20 years our rugged, off-the-shelf USB hubs and serial products are ready to go for your next project.

Within every great machine, lives Coolgear. - At Coolgear, we're just as passionate about building great products as you are. That's why we aim to meet or exceed your build specs every time.,

Advanced Engineering - Coolgear painstakingly sources high-quality components, oversees all manufacturing methods, and conducts rigorous testing to ensure all our products are industrial-grade. This means greater duty cycle, zero data loss, and longer lasting builds. We promise.,

PRODUCT SPECIFICATIONS

Looking for product documentation?

View CAD Models, Data sheet and Drawings here >



Power Input Voltage +5V DC

Country of Origin Taiwan

Certifications RoHS, TAA

Color Beige

Physical Mounting Style Surface / Wall Mount, Din-Rail Mount

Characteristics Ports 4 USB Ports

Screw Lock Compatible Yes

Software OS Support Win 7, Win 8, Win 10, Win 11, Linux, Mac OSX

Environmental Operating Temperature 0C to 70C

Product

Warranty 1 year from date of purchase

Downstream USB Ports 4 Type-A Female USB Hardware

Upstream USB Ports 1 Type-B Female USB

Performance & Isolated/Surge Protected Yes

Safety Max Data Transfer Rate 5Gbps

USB Interface USB 3.1

Connector USB 3.0 Type-B Female, USB Type-A Female

UPC 045079159969 **Other Data**

Series DTS-UH (Desktop Series Hubs)

Weight 1.387 lbs

Dimensions 9.625 × 6.625 × 2.250 in

Ready to Buy? Let's get to work!

Purchase order lets set you up.

Online with Credit card Orders shipped same day!

*orders placed prior to 3:30pm EST

⁽ <u>1-888-688-2188 (Toll free)</u>

sales@coolgear.com