

4 Port USB to RS485 High Speed Adapter w/12V DC Power Supply



USB to RS485 Adapter with Failed Signal Check

Model No. CG-UHS4P485





The USB to RS485 adapter installs automatically once connected to a USB port. When a serial device is connected to it, it will check for a fail signal indicated by a RED LED. With many application uses, this USB to RS485 serial adapter is mountable and includes an attached USB cable. This USB to RS485 adapter provides instant connectivity to communication devices for factory automation equipment, multidrop data collection devices, barcode readers, time clocks, scales, and more in harsh, rugged environments

- LEDs indicate operation mode, port status, activity and error for easy port monitoring and diagnosis
- Serial port protected with surge protection of 15kV
- Includes 12VDC power adapter with locking screw terminal power jack for reliable connection
- Each RS-485 port with 2kb receive buffer and 2kb transmit buffer

Interested? LEARN MORE >

Questions? Speak to an engineering expert today!

Our on site engineers are ready to help you with your build.

¹ 1-727-209-1300 (Local) **expert@coolgear.com**



We Speak Your Speak - When you reach out to our support, you'll find yourself in the hands of a solution-oriented, knowledgeable expert ready to answer whatever question you throw at them. Go ahead, test us.

We're Ready For Integration, Every Time. - Coolgear streamlines the task of selecting charging and connectivity products. For over 20 years our rugged, off-the-shelf USB hubs and serial products are ready to go for your next project.

Within every great machine, lives Coolgear. - At Coolgear, we're just as passionate about building great products as you are. That's why we aim to meet or exceed your build specs every time.,

Advanced Engineering - Coolgear painstakingly sources high-quality components, oversees all manufacturing methods, and conducts rigorous testing to ensure all our products are industrial-grade. This means greater duty cycle, zero data loss, and longer lasting builds. We promise.,

PRODUCT SPECIFICATIONS

Looking for product documentation?

View CAD Models, Data sheet and Drawings here >



Environmental Operating Temperature 0 to 60C

Performance Isolated/Surge Protected Yes

Input Voltage +9~48V DC

Adapter Power External

Software OS Support Win-2000, Linux, Mac OSX, Win 10, Win 7, Win 8, Win 8.1,

 $Win\,Vista,Win\,XP$

Serial Standards RS485

Serial Ports 4

USB Type USB 2.0

USB Isolated/Surge Protected Yes

Supported Data Speed 300bps to 921.6kbps

Color Black

Item Dimensions (L × W ×

H)

63 x 85 x 23mm (WxLxH)

Mechanical , ltem Weight .46 lbs.

Mounting Style Din-Rail, Surface Mount

Ports 4 Serial Ports
UPC 045079161191
Connector 6-Pin Terminal Block

Other Data
Weight 1.18 lbs

Dimensions 11.250 × 5.750 × 2.375 in

Ready to Buy? Let's get to work!

Purchase order lets set you up.

Online with Credit card Orders shipped same day!

*orders placed prior to 3:30pm EST

1-888-688-2188 (Toll free)

sales@coolgear.com