

4 Port USB 3.2 Gen 1 Micro Hub w/ Variable Voltage & ESD Surge Protection



Industrial Grade | +7~48V DC Input | Surface Mountable | 5 Gbps

Model No. CG-MIC4P31HVV





- **Protect Your Equipment:** The 4-port hub features 15kV ESD surge protection to keep your connected peripherals safe from harm.
- Super Fast Speeds: This USB hub is 3.2 Gen 1 compliant, ensuring super-fast 5Gbps data transfer speeds. It supports super speed, high speed and full speed which enables it to be compatible with USB 2.0 / 1.1.
- Small-Scale Quality: Housed in a compact steel chassis, the 4-port hub is perfect for discreet installations in offices, labs, warehouses, heavy machinery, automation equipment, and other industrial applications.
- Upstream: 1 USB port, Type B connector
- Downstream: 4 USB ports, Type A connectors
- Power Connector: 2-Pin Terminal Block
- Mounting Options: Wall & Surface

Interested? LEARN MORE →

Questions? Speak to an engineering expert today!

Our on site engineers are ready to help you with your build.

[€] 1-727-209-1300 (Local) [∞] expert@coolgear.com



We Speak Your Speak - When you reach out to our support, you'll find yourself in the hands of a solutionoriented, knowledgeable expert ready to answer whatever question you throw at them. Go ahead, test us. We're Ready For Integration, Every Time. - Coolgear streamlines the task of selecting charging and connectivity products. For over 20 years our rugged, off-the-shelf USB hubs and serial products are ready to go for your next project.

Within every great machine, lives Coolgear. - At Coolgear, we're just as passionate about building great products as you are. That's why we aim to meet or exceed your build specs every time.,

Advanced Engineering - Coolgear painstakingly sources high-quality components, oversees all manufacturing methods, and conducts rigorous testing to ensure all our products are industrial-grade. This means greater duty cycle, zero data loss, and longer lasting builds. We promise.,

PRODUCT SPECIFICATIONS



Identifier	Product Type	Hubs > USB 3.1 Hubs
Environmental	Operating Temperature	0°C to 55°C (32°F to 131°F)
	Storage Temperature	-20°C to 85°C (-4°F to 185°F)
	Humidity	5% ~ 95% (non-condensing)
Performance	ESD Protection	15KV Surge Protection for Each Port
	Isolated/Surge Protected	Y
	Max Data Transfer Rate	5Gbps
	Chipset	GL 3522
Hardware	Charging Protocols	Charging Downstream Port (CDP), Dedicated Charging Port (DCP), Standard Downstream Port (SDP)
	LED Indicators	Power
Product Information	Warranty	1 year from date of purchase
	Input Voltage	+7~48V DC
Power	Power Source	2-Pin Terminal Block, AC Adapter Not Included
	Idle Consumption	0.63mA @ 12V Terminal Power
	External Power Required	No
Software	OS Support	Win 11, Linux, Mac OSX, Win 10, Win 7, Win 8
What's in the Box	Package Contents	2-Pin Terminal Block, Hub, Mounting Plate, Screw Pack, USB- A to USB-B Cable
USB	USB Type	USB 3.2 Gen 1
	Upstream USB Ports	1 Type-B Female USB
	Downstream USB Ports	4 Type-A Female USB
	Isolated/Surge Protected	Y
	Color	Black
Mechanical	Item Dimensions (L × W × H)	3.22 × 1.82 × 0.99 in.
	Item Weight	0.32 lbs.
	Mounting Style	Surface / Wall Mount
	Ports	4 USB Ports
Compliance	Material of Construction	Galvanized Steel
	Country of Origin	Taiwan
	Certifications	<u>REACH, TAA Hubs, RoHS</u>
Other Data	Connector	USB 3.0 Type-B Female, USB Type-A Female
	UPC	045079161207
	Weight	.84 lbs
	Dimensions	8.00 × 6.625 × 1.250 in

Ready to Buy? Let's get to work!

*orders placed prior to 3:30pm EST

sales@coolgear.com