

6 Port USB 3.2 Gen 1 Type-C Hub w/ Over Current Protection & Port Status LEDs



Industrial Grade | +9~30V DC Input | Surface Mountable | DIN Rail | 5 Gbps

Model No. CG-6PU3DH-C





- Superior Build Quality: Housed in a rugged steel chassis with optional mountable flanges, the 6-port hub is perfect for installations in offices, labs, warehouses, heavy machinery, automation equipment, and other industrial applications.
- Super Fast Speeds: This USB Type-C hub is 3.2 Gen 1 compliant, ensuring super-fast 5Gbps data transfer speeds. It supports super speed, high speed and full speed which enables it to be compatible with 2.0 / 1.1.
- Check Your Ports' Status: Quickly check the status of each port individually with built in LED indicators.
- Upstream: 1 USB port, Type B connector
- **Downstream:** 4 USB ports, Type A connectors, 2 USB ports, Type-C connectors
- Power Connector: 2-Pin Terminal Block
- LED Indicators: 6 LEDs for each downstream port to indicate the current bus
- Mounting Options: Desktop, Wall, Surface & DIN Rail

Interested? LEARN MORE →

Questions? Speak to an engineering expert today!

Our on site engineers are ready to help you with your build.

1-727-209-1300 (Local) expert@coolgear.com



We Speak Your Speak - When you reach out to our support, you'll find yourself in the hands of a solution-oriented, knowledgeable expert ready to answer whatever question you throw at them. Go ahead, test us.

We're Ready For Integration, Every Time. - Coolgear streamlines the task of selecting charging and connectivity products. For over 20 years our rugged, off-the-shelf USB hubs and serial products are ready to go for your next project.

Within every great machine, lives Coolgear. - At Coolgear, we're just as passionate about building great products as you are. That's why we aim to meet or exceed your build specs every time.,

Advanced Engineering - Coolgear painstakingly sources high-quality components, oversees all manufacturing methods, and conducts rigorous testing to ensure all our products are industrial-grade. This means greater duty cycle, zero data loss, and longer lasting builds. We promise.,

PRODUCT SPECIFICATIONS

Looking for product documentation?

View CAD Models, Data sheet and Drawings here >



Operating Temperature 0°C to 45°C

Environmental Storage Temperature -20°C to 70°C

Humidity 0% ~ 90% (non-condensing)

Max Data Transfer Rate 5Gbps
Performance

Over Current Protection Y

Chipset GL 3522

Charging Downstream Port (CDP), Dedicated Charging Port

Charging Protocols (DCP)

LED Indicators Port Status, Power
Per USB Port Current 900mA maximum

Product Information

Hardware

Warranty 1 year from date of purchase

Input Voltage +9~30V DC

Over Current Protection Y

Power Source 2-Pin Terminal Block, AC Adapter Not Included

Idle Consumption 0.35mA @ 24V Terminal Power, 0.66mA @ 12V Terminal

Power

External Power Required No

Software OS Support Win 11, Linux, Mac OSX, Win 10, Win 7, Win 8

What's in the Box Package Contents

2-Pin Terminal Block, Hub, Mounting Plate, Screw Pack, USB-

A to USB-B Cable

USB Type USB 3.2 Gen 1

USB Upstream USB Ports 1 Type-B Female USB

Downstream USB Ports 2 Type-C Female USB, 4 Type-A Female USB

Color Black, Green

Item Dimensions (L × W ×

H)

123mm × 68mm × 30mm

Mechanical Item Weight 290g (0.64 lbs.)

Mounting Style Desktop, Surface / Wall Mount, Din-Rail Mount

Ports 6 USB Ports

Material of Construction Galvanized Steel

Country of Origin Taiwan
Compliance

Certifications REACH, CE, FCC, RoHS

UPC 045079162808

Other Data

Series

DTS-UH (Desktop Series Hubs)

Weight 1.0125 lbs

Dimensions $6.25 \times 4.25 \times 2$ in

Ready to Buy? Let's get to work!

Purchase order lets set you up.

1-888-688-2188 (Toll free)

Online with Credit card Orders shipped same day!

*orders placed prior to 3:30pm EST

*orders placed prior to 3:30pm EST