

6 port Managed USB 2.0 Hub w/ 15KV ESD Surge Protection



Industrial Grade | +7~48V DC Input | Surface Mountable | DIN Rail | 480 Mbps | Screw Lock

Model No. CG-6PU2MGD





- Advanced Protection: The 7-port USB 2.0 hub protects your device with advanced ESD protection. Built-in 15kV ESD surge protection offers you security and assurance that your connected devices will be protected.
- **High Speeds:** This USB hub is 2.0 compliant, ensuring fast 480Mbps data transfer speeds. It supports high speed and full speed which enables it to be compatible with USB 1.1.
- Port Management Software: Control each individual ports' status, turn bus power on/off, and even reset the entire hub through the hub's management software which supports Windows, Mac, and Linux operating systems
- Upstream: 1 USB port, Type B connector, Screw-lock type
- Downstream: 6 USB ports, Type A connectors, Screw-lock type
- **LED Indicators:** 6 LEDs for each downstream port to indicate the current bus
- Mounting Options: Wall, Surface, and DIN Rail
- Supply Current: 500mA max. per channel

Interested? LEARN MORE →

Questions? Speak to an engineering expert today!

Our on site engineers are ready to help you with your build.

¹ 1-727-209-1300 (Local) **expert@coolgear.com**



We Speak Your Speak - When you reach out to our support, you'll find yourself in the hands of a solution-oriented, knowledgeable expert ready to answer whatever question you throw at them. Go ahead, test us.

We're Ready For Integration, Every Time. - Coolgear streamlines the task of selecting charging and connectivity products. For over 20 years our rugged, off-the-shelf USB hubs and serial products are ready to go for your next project.

Within every great machine, lives Coolgear. - At Coolgear, we're just as passionate about building great products as you are. That's why we aim to meet or exceed your build specs every time.,

Advanced Engineering - Coolgear painstakingly sources high-quality components, oversees all manufacturing methods, and conducts rigorous testing to ensure all our products are industrial-grade. This means greater duty cycle, zero data loss, and longer lasting builds. We promise.,

PRODUCT SPECIFICATIONS

Looking for product documentation?

View CAD Models, Data sheet and Drawings here >



Operating Temperature 0°C to 60°C (32 to 140°F)

Environmental Storage Temperature -20 to 75°C (-4 to 167°F)

Humidity 5% ~ 95% (non-condensing)

ESD Protection 15KV Surge Protection for Each Port **Performance**

Max Data Transfer Rate 480Mbps

Chipset GL 852GT

Charging Protocols Hardware

Charging Downstream Port (CDP), Dedicated Charging Port

(DCP)

LED Indicators Port Status, Power

Per USB Port Current 500mA

Product Information

Warranty 1 year from date of purchase

Input Voltage +7~48V DC

Power Source 2-Pin Terminal Block, AC Adapter Not Included

External Power Required Yes

OS Support Win 11, Linux, Win 10, Win 7, Win 8

Software Managing Software

Utilities

cusba: ARM Based Linux Controller Utility, CUSBC: Windows Console Command Control Utility, cusbi: Intel x86-64 Based

Linux Control Utility, USBCTL: Windows GUI

What's in the Box Package Contents

DIN Rail Clip(s), Hub, Screw Pack, USB-A to Screw Lock USB-B

Cable

USB Type USB 2.0

Upstream USB Ports 1 Type-B Female USB USB

Downstream USB Ports 6 Type-A Female USB

Screw Lock Compatible Yes

Color Black

Item Dimensions (L × W ×

H)

5.2 × 2.42 × 1.43 in.

Mechanical Item Weight 0.6 lbs.

Mounting Style Surface / Wall Mount, Din-Rail Mount

Ports 6 USB Ports

Material of Construction Galvanized Steel

Compliance Country of Origin Taiwan
Certifications RoHS

UPC 045079163089

Series MDS-UH (Managed Hub Series)
Other Data

Weight 1.0875 lbs

Dimensions 9.649 × 6.655 × 2.249 in

Purchase order lets set you up.

Online with Credit card Orders shipped same day!

*orders placed prior to 3:30pm EST

1-888-688-2188 (Toll free)

sales@coolgear.com