




6 Port Managed USB 2.0 Hub w/ 15KV ESD Surge Protection



Industrial Grade | +7~48V DC Input | Surface Mountable | DIN Rail | 480 Mbps | Screw Lock

Model No. CG-6PU2MGD



[View more images here >](#)

- **Advanced Protection:** The 7-port USB 2.0 hub protects your device with advanced ESD protection. Built-in 15kV ESD surge protection offers you security and assurance that your connected devices will be protected.
- **High Speeds:** This USB hub is 2.0 compliant, ensuring fast 480Mbps data transfer speeds. It supports high speed and full speed which enables it to be compatible with USB 1.1.
- **Port Management Software:** Control each individual ports' status, turn bus power on/off, and even reset the entire hub through the hub's management software which supports Windows, Mac, and Linux operating systems
- **Upstream:** 1 USB port, Type B connector, Screw-lock type
- **Downstream:** 6 USB ports, Type A connectors, Screw-lock type
- **LED Indicators:** 6 LEDs for each downstream port to indicate the current bus
- **Mounting Options:** Wall, Surface, and DIN Rail
- **Supply Current:** 500mA max. per channel

Interested? LEARN MORE →

Questions? Speak to an engineering expert today!

Our on site engineers are ready to help you with your build.

☎ [1-727-209-1300](tel:1-727-209-1300) (Local) ✉ expert@coolgear.com



We Speak Your Speak - When you reach out to our support, you'll find yourself in the hands of a solution-oriented, knowledgeable expert ready to answer whatever question you throw at them. Go ahead, test us.

We're Ready For Integration, Every Time. - Coolgear streamlines the task of selecting charging and connectivity products. For over 20 years our rugged, off-the-shelf USB hubs and serial products are ready to go for your next project.

Within every great machine, lives Coolgear. - At Coolgear, we're just as passionate about building great products as you are. That's why we aim to meet or exceed your build specs every time.,

Advanced Engineering - Coolgear painstakingly sources high-quality components, oversees all manufacturing methods, and conducts rigorous testing to ensure all our products are industrial-grade. This means greater duty cycle, zero data loss, and longer lasting builds. We promise.,

PRODUCT SPECIFICATIONS

Looking for product documentation?

[View CAD Models, Data sheet and Drawings here >](#)




| | | |
|---------------------|-----------------------------|---|
| Environmental | Operating Temperature | 0°C to 60°C (32 to 140°F) |
| | Storage Temperature | -20 to 75°C (-4 to 167°F) |
| | Humidity | 5% ~ 95% (non-condensing) |
| Performance | ESD Protection | 15KV Surge Protection for Each Port |
| | Max Data Transfer Rate | 480Mbps |
| | Chipset | GL 852GT |
| Hardware | Charging Protocols | Charging Downstream Port (CDP), Dedicated Charging Port (DCP) |
| | LED Indicators | Port Status, Power |
| | Per USB Port Current | 500mA |
| Product Information | Warranty | 1 year from date of purchase |
| | Input Voltage | +7~48V DC |
| Power | Power Source | 2-Pin Terminal Block, AC Adapter Not Included |
| | External Power Required | Yes |
| | Max Wattage | 17.5W |
| Software | OS Support | Win 11, Linux, Win 10, Win 7, Win 8 |
| | Managing Software Utilities | cusba: ARM Based Linux Controller Utility, CUSBC: Windows Console Command Control Utility, cusbi: Intel x86-64 Based Linux Control Utility, USBCTL: Windows GUI |
| | Package Contents | DIN Rail Clip(s), Hub, Screw Pack, USB-A to Screw Lock USB-B Cable |
| What's in the Box | USB Type | USB 2.0 |
| | Upstream USB Ports | 1 Type-B Female USB |
| | Downstream USB Ports | 6 Type-A Female USB |
| USB | Screw Lock Compatible | Yes |
| | Color | Black |
| | Item Dimensions (L × W × H) | 5.2 × 2.42 × 1.43 in. |
| Mechanical | Item Weight | 0.631 lbs. |
| | Mounting Style | Surface / Wall Mount, Din-Rail Mount |
| | Ports | 6 USB Ports |
| Compliance | Material of Construction | Galvanized Steel |
| | Country of Origin | Taiwan |
| | Certifications | REACH , RoHS |
| Other Data | UPC | 045079163089 |
| | Series | MDS-UH (Managed Hub Series) |
| | Weight | 1.125 lbs |
| | Dimensions | 9.649 × 6.655 × 2.249 in |

Ready to Buy? Let's get to work!

Purchase order lets set you up.

Online with Credit card Orders shipped same day!

*orders placed prior to 3:30pm EST

 **1-888-688-2188 (Toll free)**

 **sales@coolgear.com**