

# 6 Port USB 3.2 Gen 1 Hub w/ Over Current Protection & Port Status LEDs



Industrial Grade | +9~30V DC Input | Surface Mountable | DIN Rail | 5 Gbps

Model No. CG-6PU3DH-A





- Superior Build Quality: Housed in a rugged steel chassis with optional mountable flanges, the 6-port hub is perfect for installations in offices, labs, warehouses, heavy machinery, automation equipment, and other industrial applications.
- Super Fast Speeds: This USB hub is 3.2 Gen 1 compliant, ensuring super-fast 5Gbps data transfer speeds. It supports super speed, high speed and full speed which enables it to be compatible with 2.0 / 1.1.
- Check Your Ports' Status: Quickly check the status of each port individually with built in LED indicators.
- Upstream: 1 USB port, Type B connector
- **Downstream:** 6 USB ports, Type A connectors
- Power Connector: 2-Pin Terminal Block
- **LED Indicators:** 6 LEDs for each downstream port to indicate the current bus
- Mounting Options: Desktop, Wall, Surface & DIN Rail

Interested? LEARN MORE →

# **Questions?** Speak to an engineering expert today!

Our on site engineers are ready to help you with your build.

<sup>1</sup> 1-727-209-1300 (Local) **expert@coolgear.com** 



We Speak Your Speak - When you reach out to our support, you'll find yourself in the hands of a solution-oriented, knowledgeable expert ready to answer whatever question you throw at them. Go ahead, test us.

We're Ready For Integration, Every Time. - Coolgear streamlines the task of selecting charging and connectivity products. For over 20 years our rugged, off-the-shelf USB hubs and serial products are ready to go for your next project.

**Within every great machine, lives Coolgear.** - At Coolgear, we're just as passionate about building great products as you are. That's why we aim to meet or exceed your build specs every time.,

**Advanced Engineering** - Coolgear painstakingly sources high-quality components, oversees all manufacturing methods, and conducts rigorous testing to ensure all our products are industrial-grade. This means greater duty cycle, zero data loss, and longer lasting builds. We promise.,

# PRODUCT SPECIFICATIONS

### Looking for product documentation?

View CAD Models, Data sheet and Drawings here >



Operating Temperature 0°C to 45°C

**Environmental Storage Temperature** -20°C to 70°C

**Humidity** 0% ~ 90% (non-condensing)

Max Data Transfer Rate 5Gbps
Performance

Over Current Protection Y

Chipset GL 3522

Charging Protocols

Charging Downstream Port (CDP), Dedicated Charging Port

(DCP)

LED Indicators Port Status, Power
Per USB Port Current 900mA maximum

Product Information

**Hardware** 

Warranty 1 year from date of purchase

Input Voltage +9~30V DC

**Over Current Protection** Y

Power Source

2-Pin Terminal Block, AC Adapter Not Included

Idle Consumption 0.35mA @ 24V Terminal Power, 0.66mA @ 12V Terminal

Power

**External Power Required** Yes

Software OS Support Win 11, Linux, Mac OSX, Win 10, Win 7, Win 8

What's in the Box Package Contents

2-Pin Terminal Block, Hub, Mounting Plate, Screw Pack, USB-

A to USB-B Cable

**USB Type** USB 3.2 Gen 1

USB Upstream USB Ports 1 Type-B Female USB

**Downstream USB Ports** 6 Type-A Female USB

Color Black, Green

Item Dimensions (L × W ×

H)

123mm × 68mm × 30mm

Mechanical Item Weight 10.3 oz.

**Mounting Style** Desktop, Surface / Wall Mount, Din-Rail Mount

Ports 6 USB Ports

Material of Construction Galvanized Steel

Country of Origin Taiwan
Compliance

**Certifications** REACH, RoHS

**UPC** 045079162815

Other Data

Series 

DTS-UH (Desktop Series Hubs)

 Weight
 1.00625 lbs

 Dimensions
 6.25 × 4.25 × 2 in

# Ready to Buy? Let's get to work!

Purchase order lets set you up.

1-888-688-2188 (Toll free)

Online with Credit card Orders shipped same day!

\*orders placed prior to 3:30pm EST

\*orders placed prior to 3:30pm EST