

7 Port Managed USB 3.2 Gen 1 Hub w/ 15KV ESD Surge Protection



Industrial Grade | +7~24V DC Input | Surface Mountable | DIN Rail | 5 Gbps | Screw Lock

Model No. CG-7PU3MGD



- Advanced Protection: The 7-port USB 3.2 Gen 1 hub protects your device with advanced ESD protection. Built-in 15kV ESD surge protection offers you security and assurance that your connected devices will be protected.
- Super Fast Speeds: This USB hub is 3.2 Gen 1 compliant, ensuring super-fast 5Gbps data transfer speeds. It supports super speed, high speed and full speed which enables it to be compatible with USB 2.0 / 1.1.
- Port Management Software: Control each individual ports' status, turn bus power on/off, and even reset the entire hub through the hub's management software which supports Windows, Mac, and Linux operating systems
- Upstream: 1 USB port, Type B connector, Screw-lock type
- Downstream: 7 USB ports, Type A connectors, Screw-lock type
- LED Indicators: 7 LEDs for each downstream port to indicate the current bus
- Mounting Options: Wall, Surface, and DIN Rail
- Supply Current: 1.5A max. per channel

Interested? LEARN MORE →

Questions? Speak to an engineering expert today! Our on site engineers are ready to help you with your build.

[€] <u>1-727-209-1300</u> (Local) ^I expert@coolgear.com



We Speak Your Speak - When you reach out to our support, you'll find yourself in the hands of a solutionoriented, knowledgeable expert ready to answer whatever question you throw at them. Go ahead, test us. We're Ready For Integration, Every Time. - Coolgear streamlines the task of selecting charging and connectivity products. For over 20 years our rugged, off-the-shelf USB hubs and serial products are ready to go for your next project.

Within every great machine, lives Coolgear. - At Coolgear, we're just as passionate about building great products as you are. That's why we aim to meet or exceed your build specs every time.,

Advanced Engineering - Coolgear painstakingly sources high-quality components, oversees all manufacturing methods, and conducts rigorous testing to ensure all our products are industrial-grade. This means greater duty cycle, zero data loss, and longer lasting builds. We promise.,

PRODUCT SPECIFICATIONS

Environmental		0°C to 60°C (32 to 140°F)
	Storage Temperature	-20 to 75°C (-4 to 167°F)
	Humidity	5% ~ 95% (non-condensing)
Performance	Altitude	Up to 2000m
	ESD Protection	15KV Surge Protection for Each Port
	Max Data Transfer Rate	5Gbps
	Over Current Protection	Y
	Chipset	GL 3523
Hardware	Charging Protocols	Apple 2.4A, BC 1.2, Charging Downstream Port (CDP), Dedicated Charging Port (DCP), Samsung
	LED Indicators	Port Status, Power
	Per USB Port Current	1.5 A
Product Information	Warranty	1 year from date of purchase
	Input Voltage	+7~48V DC
	Over Current Protection	Y
Power	Power Source	2-Pin Terminal Block, AC Adapter Not Included, DC Barrel Jack 2.1mm ID x 5.5mm OD
	Idle Consumption	1.49mA @ 12V Terminal Power
	External Power Required	Yes
Software	OS Support	Win 11, Linux, Mac OSX, Win 10, Win 7, Win 8
	Managing Software Utilities	cusba: ARM Based Linux Controller Utility, CUSBC: Windows Console Command Control Utility, cusbi: Intel x86-64 Based Linux Control Utility, USBCTL: Windows GUI
What's in the Box	Package Contents	2-Pin Terminal Block, DIN Rail Clip(s), Hub, Screw Pack, USB- A to Screw Lock USB-B Cable
USB	USB Type	USB 3.2 Gen 1
	Upstream USB Ports	1 Type-B Female USB
	Downstream USB Ports	7 Type-A Female USB
	Screw Lock Compatible	Yes
	Color	Black
Mechanical	ltem Dimensions (L × W × H)	6.41× 2.16 × 1.22 in.
	Item Weight	0.625 lbs.
	Mounting Style	Surface / Wall Mount, Din-Rail Mount
	Material of Construction	Galvanized Steel
Compliance	Country of Origin	Taiwan
	Certifications	RoHS
Other Data	UPC	045079163102
	Series	MDS-UH (Managed Hub Series)
	Weight	1.1063 lbs
	Dimensions	9.649 × 6.655 × 2.249 in

Ready to Buy? Let's get to work!

Purchase order lets set you up.

Online with Credit card Orders shipped same day!

*orders placed prior to 3:30pm EST

- ⁽ <u>1-888-688-2188 (Toll free)</u>
- sales@coolgear.com