





7 Port USB 3.2 Gen 1 Hub PCBA w/ ESD Surge Protection



+9~24V DC Input | 5 Gbps

Model No. GM-HU37-PCBA



- **Protect Your Equipment:** The 7-port USB 3.2 Gen 1 features 15kV ESD surge protection per port to keep your connected peripherals safe from harm.
- **Super Fast Speeds:** This USB hub PCBA is 3.2 Gen 1 compliant, ensuring super-fast 5Gbps data transfer speeds. It supports super speed, high speed and full speed which enables it to be compatible with USB 2.0 / 1.1.
- **Upstream:** 1 USB port, Type B connector
- **Downstream:** 7 USB ports, Type A connectors
- **Power Connector:** 3-Pin Terminal Block, DC Barrel
- **LEDs:** Power

Interested? [LEARN MORE →](#)



Questions? Speak to an engineering expert today!

Our on site engineers are ready to help you with your build.

☎ [1-727-209-1300](tel:1-727-209-1300) (Local) ✉ expert@coolgear.com



We Speak Your Speak - When you reach out to our support, you'll find yourself in the hands of a solution-oriented, knowledgeable expert ready to answer whatever question you throw at them. Go ahead, test us.

We're Ready For Integration, Every Time. - Coolgear streamlines the task of selecting charging and connectivity products. For over 20 years our rugged, off-the-shelf USB hubs and serial products are ready to go for your next project.

Within every great machine, lives Coolgear. - At Coolgear, we're just as passionate about building great products as you are. That's why we aim to meet or exceed your build specs every time.,

Advanced Engineering - Coolgear painstakingly sources high-quality components, oversees all manufacturing methods, and conducts rigorous testing to ensure all our products are industrial-grade. This means greater duty cycle, zero data loss, and longer lasting builds. We promise.,

PRODUCT SPECIFICATIONS

Looking for product documentation?

[View CAD Models, Data sheet and Drawings here >](#)



Environmental	Operating Temperature	0°C to 40°C
	Storage Temperature	-20°C to 50°C
	Humidity	5% ~ 85% (non-condensing)
	ESD Protection	15KV Surge Protection for Each Port
Performance	Isolated/Surge Protected	Yes
	Max Data Transfer Rate	5Gbps
	Over Current Protection	Y
	Over Voltage Protection	Y
Hardware	Surge Protection	600W
	Chipset	VIA VL811+
	LED Indicators	Power
Product Information	Warranty	1 year from date of purchase
	Input Voltage	+9~24V DC
Power	Over Current Protection	Y
	Over Voltage Protection	Y
	Power Source	3-Pin Terminal Block, AC Adapter Not Included, DC Barrel Jack
Software	OS Support	OS Independent; No Additional Drivers Required
	USB Type	USB 3.2 Gen 1
USB	Upstream USB Ports	1 Type-B Female USB
	Downstream USB Ports	7 Type-A Female USB
	Isolated/Surge Protected	Yes
Mechanical	Supported Data Speed	5Gb/sec, 480Mb/sec, 12Mb/sec, 1.5Mb/sec
	Item Dimensions (L × W × H)	5.46 × 2.52 × 0.72 in.
	Item Weight	0.181 lbs.
Compliance	Ports	7 USB Ports
	Country of Origin	China
Other Data	UPC	045079163560
	Weight	0.20625 lbs
	Dimensions	8 × 6 × 1 in

Ready to Buy? Let's get to work!

Purchase order lets set you up.

Online with Credit card Orders shipped same day!

*orders placed prior to 3:30pm EST

☎ **1-888-688-2188 (Toll free)**

✉ **sales@coolgear.com**