



# 72 Inch USB to DB-9 Serial High Speed Adapter with FTDI Chipset



USB to RS232 Adapter - FTDI Chipset

Model No. USBG-RS232-F72



For computer users that require one new or additional RS-232 connection without the extra cable length. This cable features RX/TX and Power LEDs and utilizes the FTDI Chipset.

- Supports use on Laptop or desktop computer using USB to RS232 connections.
- Supports peripherals such as bar code readers, digital cameras, modems and more.
- Installs as a standard Windows COM Port.
- COM port number assigned can be changed to any COM port number required

Interested? [LEARN MORE →](#)



[View more images here >](#)

## Questions? Speak to an engineering expert today!

Our on site engineers are ready to help you with your build.

☎ [1-727-209-1300](tel:1-727-209-1300) (Local) ✉ [expert@coolgear.com](mailto:expert@coolgear.com)



**We Speak Your Speak** - When you reach out to our support, you'll find yourself in the hands of a solution-oriented, knowledgeable expert ready to answer whatever question you throw at them. Go ahead, test us.

**We're Ready For Integration, Every Time.** - Coolgear streamlines the task of selecting charging and connectivity products. For over 20 years our rugged, off-the-shelf USB hubs and serial products are ready to go for your next project.

**Within every great machine, lives Coolgear.** - At Coolgear, we're just as passionate about building great products as you are. That's why we aim to meet or exceed your build specs every time.,

**Advanced Engineering** - Coolgear painstakingly sources high-quality components, oversees all manufacturing methods, and conducts rigorous testing to ensure all our products are industrial-grade. This means greater duty cycle, zero data loss, and longer lasting builds. We promise.,

# PRODUCT SPECIFICATIONS

Looking for product documentation?

[View CAD Models, Data sheet and Drawings here >](#)



Physical Characteristics	Color	Smoke
	Length	6ft
	Ports	1 Serial Port
	Material of Construction	Plastic
	RS Signals	TxD, RxD, RTS, CTS, DSR, DTR, DCD, RI, GND
	Serial Standards	RS232
	Baud Rate	921.6K bps
Serial Attributes	FIFO Receive	128 bytes
	FIFO Transmit	256 bytes
	Data Bits	7, 8
	Parity	None, Even, Odd, Mark, Space
	Stop Bits	1, 2
	Flow Control	Hardware (RTS, CTS), XON/XOFF
	Serial Ports	1
Software	OS Support	Win XP, Win Vista, Win 7, Win 8, Win 10, Win 11, Linux, Mac OSX
Hardware	Chipset	FTDI
	Upstream USB Ports	1 Type-A Male USB
	Warranty	1 year from date of purchase
Other Data	Chip Model	FT232BL
	Connector	DB9 Male w/ Nuts
	USB Interface	USB 2.0
	Weight	.4 lbs
	Dimensions	7 × 4 × 1.5 in

## Ready to Buy? Let's get to work!

**Purchase order** lets set you up.

**Online with Credit card** Orders shipped same day!

\*orders placed prior to 3:30pm EST

📞 **1-888-688-2188 (Toll free)**

✉ **sales@coolgear.com**