



ChargeIT! Mini Desktop 75W Dual Port USB-A & USB-C PD Charger w/ PPS & QC4.0 Support



*Optional Surface Mounting Bracket Installed

Model No. CG-CMD60W



[View more
images here >](#)

Industrial Grade | +9~24V DC Input | Over Voltage & Current Protection

- **Simultaneous Power:** Charge 2 iPads, iPhones or other USB-charged in charge mode devices, while the built in PD chipset dynamically detects devices to deliver optimum power level for maximum battery life and performance.
- **Quick Charge:** Provides up to 75W of combined charging. The USB-A port supports QC 3.0 while the USB-C port supports QC 4.0.
- **Workstation Charging:** Use the optional rubber feet for desktop placement or the included mounting panel for surface mount installs.
- **Superior Build Quality:** Housed in a rugged metal chassis, the 2-port charger hub is perfect for installations on desks, in offices, labs, studios, and classrooms. Perfect for personal workstations.
- **Downstream:** 1 USB Type-A QC Port, 1 USB Type-C PD Port
- **Power Connector:** 2-Pin Terminal Block
- **Mounting Options:** Wall, Surface, & Desktop
- **LED Indicators:** Power

Interested? LEARN MORE →

Questions? Speak to an engineering expert today!

Our on site engineers are ready to help you with your build.

☎ **1-727-209-1300** (Local) ✉ **expert@coolgear.com**



We Speak Your Speak - When you reach out to our support, you'll find yourself in the hands of a solution-oriented, knowledgeable expert ready to answer whatever question you throw at them. Go ahead, test us.

We're Ready For Integration, Every Time. - Coolgear streamlines the task of selecting charging and connectivity products. For over 20 years our rugged, off-the-shelf USB hubs and serial products are ready to go for your next project.

Within every great machine, lives Coolgear. - At Coolgear, we're just as passionate about building great products as you are. That's why we aim to meet or exceed your build specs every time.,

Advanced Engineering - Coolgear painstakingly sources high-quality components, oversees all

manufacturing methods, and conducts rigorous testing to ensure all our products are industrial-grade. This

Coolgear | Charging & Connectivity Experts
www.coolgear.com

Visit coolgear.com/support for any questions & inquiries.

means greater duty cycle, zero data loss, and longer lasting builds. We promise.,

PRODUCT SPECIFICATIONS

Looking for product documentation?

[View CAD Models, Data sheet and Drawings here >](#)



Environmental	Operating Temperature	0°C to 55°C (32°F to 131°F)
	Storage Temperature	-20 to 75°C (-4 to 167°F)
	Humidity	5% ~ 95% (non-condensing)
Performance	Over Current Protection	Y
	Over Voltage Protection	Y
Hardware	Charging Protocols	Apple 2.4A, Dedicated Charging Port (DCP), QC3.0, QC4.0, Samsung
	LED Indicators	Power
Product Information	Warranty	1 year from date of purchase
	Input Voltage	+9~24V DC
	Over Current Protection	Y
Power	Over Voltage Protection	Y
	Power Source	2-Pin Terminal Block
	Adapter Input Current	1.5A
	Adapter Input Voltage	100~240V AC
	Adapter Output Current	6A
	Adapter Output Voltage	12V DC
	External Power Required	Yes
What's in the Box	Package Contents	Mounting Plate, Power Adapter, Power Cable, Rubber Feet, Screw Pack, USB Charger
PD Profile Support	Voltage Profiles	5V/3A, 7V/2.5A, 9V/3A, 12V/3A, 15V/3A, 20V/2.99A
USB	USB Type	Type-C
	Downstream USB Ports	1 Type-A Female USB, 1 Type-C Female USB
	Color	White
	Item Dimensions (L × W × H)	2.38 × 1.97 × 1.03 in.
Mechanical	Item Weight	0.281 lbs.
	Mounting Style	Desktop, Surface / Wall Mount
	Ports	2 USB Ports
	Material of Construction	Steel
Compliance	Country of Origin	China
	UPC	045079163461
Other Data	Chip Model	Cypress CCG3PA
	Weight	1.39 lbs

Ready to Buy? Let's get to work!

[Purchase order](#) lets set you up.

[Online with Credit card](#) Orders shipped same day!

☎ **1-888-688-2188 (Toll free)**

*orders placed prior to 3:30pm EST

 sales@coolgear.com