

ChargeIT! Mini Desktop 75W Dual Port USB-A & USB-C PD Charger w/ PPS & QC4.0 Support



*Optional Surface Mounting Bracket Installed

Model No. CG-CMD60W







<u>View more</u> <u>images here ></u>

Industrial Grade | +9~24V DC Input | Over Voltage & Current Protection

- Simultaneous Power: Charge 2 iPads, iPhones or other USB-charged in charge mode devices, while the built in PD chipset dynamically detects devices to deliver optimum power level for maximum battery life and performance.
- Quick Charge: Provides up to 75W of combined charging. The USB-A port supports QC 3.0 while the USB-C port supports QC 4.0.
- Workstation Charging: Use the optional rubber feet for desktop placement or the included mounting panel for surface mount installs.
- Superior Build Quality: Housed in a rugged metal chassis, the 2-port charger hub is perfect for installations on desks, in offices, labs, studios, and classrooms. Perfect for personal workstations.
- Downstream: 1 USB Type-A QC Port, 1 USB Type-C PD
- Power Connector: 2-Pin Terminal Block
- Mounting Options: Wall, Surface, & Desktop
- LED Indicators: Power

Interested? LEARN MORE >

Questions? Speak to an engineering expert today!

Our on site engineers are ready to help you with your build.

¹ 1-727-209-1300 (Local) **expert@coolgear.com**



We Speak Your Speak - When you reach out to our support, you'll find yourself in the hands of a solution-oriented, knowledgeable expert ready to answer whatever question you throw at them. Go ahead, test us.

We're Ready For Integration, Every Time. - Coolgear streamlines the task of selecting charging and connectivity products. For over 20 years our rugged, off-the-shelf USB hubs and serial products are ready to go for your next project.

Within every great machine, lives Coolgear. - At Coolgear, we're just as passionate about building great products as you are. That's why we aim to meet or exceed your build specs every time.,

Advanced Engineering - Coolgear painstakingly sources high-quality components, oversees all



PRODUCT SPECIFICATIONS

Looking for product documentation?

View CAD Models, Data sheet and Drawings here >



Operating Temperature 0°C to 55°C (32°F to 131°F)

Environmental Storage Temperature -20 to 75°C (-4 to 167°F)

Humidity 5% ~ 95% (non-condensing)

Over Current Protection Y
Performance

Over Voltage Protection Y

Charging Protocols

Apple 2.4A, Dedicated Charging Port (DCP), QC3.0, QC4.0,

Samsung

LED Indicators Power

Product Information

Hardware

Warranty 1 year from date of purchase

Input Voltage +9~24V DC

Over Current Protection Y
Over Voltage Protection Y

Power Source 2-Pin Terminal Block

Power Adapter Input Current 1.5A

Adapter Input Voltage 100~240V AC

Adapter Output Current 6A
Adapter Output Voltage 12V DC
External Power Required Yes

What's in the Box Package Contents

Mounting Plate, Power Adapter, Power Cable, Rubber Feet,

Screw Pack, USB Charger

PD Profile Support Voltage Profiles 5V/3A, 7V/2.5A, 9V/3A, 12V/3A, 15V/3A, 20V/2.99A

USB Type Type-C

Downstream USB Ports 1 Type-A Female USB, 1 Type-C Female USB

Color White

Item Dimensions (L × W ×

H)

 $2.38 \times 1.97 \times 1.03$ in.

Mechanical Item Weight 0.281 lbs.

Mounting Style Desktop, Surface / Wall Mount

Ports 2 USB Ports

Material of Construction Steel

Compliance Country of Origin China

UPC 045079163461

Other Data Chip Model Cypress CCG3PA

Weight 1.39 lbs

Ready to Buy? Let's get to work!

Purchase order lets set you up.

Online with Credit card Orders shipped same day!

1-888-688-2188 (Toll free)