



Coolgear Labs Low Power 10W POE to Type C PD for NEST CAM IQ



Model No. CG-POE15vPD-LP



Coolgear's newest USB Type-C PoE adapter works with a Cat5/6 cable from a PoE injector connected to its RJ45 port. This extends the length of power to the Nest Cam Indoor or Nest Cam Outdoor by up to 100 meters from a power source. Offering a power output of 10 Watts USB Type C PD, use the Type-C USB port to **connect your Nest Cam, Sensors, or other Low Power USB-C device.**

- Utilizes a PoE injector for power.
- Isolated POE Active DC-DC adapter to power up USB type C devices
- Specifically designed for use with low power USB-C Power Delivery (PD) Devices
- Power Output: 10 Watts USB Type C PD
- Overload, Over Current, & Short-Circuit Protection
- Fully IEEE802.3at and IEEE802.3af compliant PoE.

Interested? LEARN MORE →



[View more images here >](#)

Questions? Speak to an engineering expert today!

Our on site engineers are ready to help you with your build.

☎ **1-727-209-1300** (Local) ✉ **expert@coolgear.com**



We Speak Your Speak - When you reach out to our support, you'll find yourself in the hands of a solution-oriented, knowledgeable expert ready to answer whatever question you throw at them. Go ahead, test us.

We're Ready For Integration, Every Time. - Coolgear streamlines the task of selecting charging and connectivity products. For over 20 years our rugged, off-the-shelf USB hubs and serial products are ready to go for your next project.

Within every great machine, lives Coolgear. - At Coolgear, we're just as passionate about building great products as you are. That's why we aim to meet or exceed your build specs every time.,

Advanced Engineering - Coolgear painstakingly sources high-quality components, oversees all manufacturing methods, and conducts rigorous testing to ensure all our products are industrial-grade. This means greater duty cycle, zero data loss, and longer lasting builds. We promise.,

PRODUCT SPECIFICATIONS

Looking for product documentation?
[View CAD Models, Data sheet and Drawings here >](#)




| | | |
|---------------------|-----------------------------|---------------------------|
| Environmental | Operating Temperature | 0°C to 60°C (32 to 140°F) |
| Power over Ethernet | PoE Standard | IEEE802.3af, IEEE802.3at |
| Performance | Over Current Protection | Y |
| Hardware | Chipset | Ijoinic |
| | LED Indicators | Connection |
| Power | Over Current Protection | Y |
| PD Profile Support | Voltage Profiles | 5V, 15V, 9V, 12V |
| | Color | White |
| Mechanical | Item Dimensions (L × W × H) | 2.52 × 1.14 × 0.98 in. |
| | UPC | 045079163379 |
| Other Data | Weight | 0.038 lbs |
| | Dimensions | 2.52 × 1.14 × 0.98 in |

Ready to Buy? Let's get to work!

Purchase order lets set you up.

Online with Credit card Orders shipped same day!

*orders placed prior to 3:30pm EST

 **1-888-688-2188 (Toll free)**

 **sales@coolgear.com**