



# Coolgear Labs Low Power 10W POE to Type C PD for NEST CAM IQ



Model No. CG-POE15vPD-LP



Coolgear's newest USB Type-C PoE adapter works with a Cat5/6 cable from a PoE injector connected to its RJ45 port. This extends the length of power to the Nest Cam Indoor or Nest Cam Outdoor by up to 100 meters from a power source. Offering a power output of 10 Watts USB Type C PD, use the Type-C USB port to **connect your Nest Cam, Sensors, or other Low Power USB-C device.**

- Utilizes a PoE injector for power.
- Isolated POE Active DC-DC adapter to power up USB type C devices
- Specifically designed for use with low power USB-C Power Delivery (PD) Devices
- Power Output: 10 Watts USB Type C PD
- Overload, Over Current, & Short-Circuit Protection
- Fully IEEE802.3at and IEEE802.3af compliant PoE.

**Interested? LEARN MORE →**



[View more images here >](#)

## Questions? Speak to an engineering expert today!

Our on site engineers are ready to help you with your build.

☎ **1-727-209-1300** (Local) ✉ **expert@coolgear.com**



**We Speak Your Speak** - When you reach out to our support, you'll find yourself in the hands of a solution-oriented, knowledgeable expert ready to answer whatever question you throw at them. Go ahead, test us.

**We're Ready For Integration, Every Time.** - Coolgear streamlines the task of selecting charging and connectivity products. For over 20 years our rugged, off-the-shelf USB hubs and serial products are ready to go for your next project.

**Within every great machine, lives Coolgear.** - At Coolgear, we're just as passionate about building great products as you are. That's why we aim to meet or exceed your build specs every time.,

**Advanced Engineering** - Coolgear painstakingly sources high-quality components, oversees all manufacturing methods, and conducts rigorous testing to ensure all our products are industrial-grade. This means greater duty cycle, zero data loss, and longer lasting builds. We promise.,

# PRODUCT SPECIFICATIONS

Looking for product documentation?  
[View CAD Models, Data sheet and Drawings here >](#)



|                     |                             |                           |
|---------------------|-----------------------------|---------------------------|
| Environmental       | Operating Temperature       | 0°C to 60°C (32 to 140°F) |
| Power over Ethernet | PoE Standard                | IEEE802.3af, IEEE802.3at  |
| Performance         | Over Current Protection     | Y                         |
| Hardware            | Chipset                     | Ijoinic                   |
|                     | LED Indicators              | Connection                |
| Power               | Over Current Protection     | Y                         |
| PD Profile Support  | Voltage Profiles            | 5V, 15V, 9V, 12V          |
|                     | Color                       | White                     |
| Mechanical          | Item Dimensions (L × W × H) | 2.52 × 1.14 × 0.98 in.    |
|                     | UPC                         | 045079163379              |
| Other Data          | Weight                      | 0.038 lbs                 |
|                     | Dimensions                  | 2.52 × 1.14 × 0.98 in     |

## Ready to Buy? Let's get to work!

Purchase order lets set you up.

Online with Credit card Orders shipped same day!

\*orders placed prior to 3:30pm EST

 **1-888-688-2188 (Toll free)**

 **[sales@coolgear.com](mailto:sales@coolgear.com)**