

Dual USB Charging Board Type-A 15 Watts x 2 | Type-C PD 30 Watts x 2 60 Watts Total – PCBA



Model No. CG-CCJPDAC60



The ChargeIT! Dual Port Charger provides an effective amount of Charging power ideal for Tablets, Cell phones, and laptops. The USB PD charger board incorporates both Standard Type-A and USB PD Type-C charging ports. The wide DC input voltage range is ideal for 12V DC and 24V DC Vehicle applications.

- DC Input Voltage: 10~28V
- Output Voltage: 3~12V, Adjustable
- Power Connector: 2-Pin Terminal Block
- Provides two USB-C PD 30 Watt PD 3.0 PPS ports or two USB-A 15 Watt ports
- Multi-protection for high reliability including ESD, overvoltage, reverse polarity installation, and over-temperature protection.

Interested? LEARN MORE →



Questions? Speak to an engineering expert today!

Our on site engineers are ready to help you with your build.

¹ 1-727-209-1300 (Local) **expert@coolgear.com**



We Speak Your Speak - When you reach out to our support, you'll find yourself in the hands of a solution-oriented, knowledgeable expert ready to answer whatever question you throw at them. Go ahead, test us.

We're Ready For Integration, Every Time. - Coolgear streamlines the task of selecting charging and connectivity products. For over 20 years our rugged, off-the-shelf USB hubs and serial products are ready to go for your next project.

Within every great machine, lives Coolgear. - At Coolgear, we're just as passionate about building great products as you are. That's why we aim to meet or exceed your build specs every time.,

Advanced Engineering - Coolgear painstakingly sources high-quality components, oversees all manufacturing methods, and conducts rigorous testing to ensure all our products are industrial-grade. This means greater duty cycle, zero data loss, and longer lasting builds. We promise.,

PRODUCT SPECIFICATIONS

Looking for product documentation?

View CAD Models, Data sheet and Drawings here >



ESD Protection 4KV Surge Protection

Performance Over Current Protection Y

Over Voltage Protection Y

Hardware Charging Protocols Apple 2.4A, Dedicated Charging Port (DCP), Samsung

Product Information

Warranty 1 year from date of purchase

Input Voltage +12~24V DC

Power Over Current Protection Y

Over Voltage Protection Y

PD Profile Support Voltage Profiles 5V/2.4A, 9V/3A, 12V/2.25A

Compliance Country of Origin China

UPC 045079163386

Other Data Weight 0.037 lbs

Dimensions $2.75 \times 2.00 \times 0.50 \text{ in}$

Ready to Buy? Let's get to work!

Purchase order lets set you up.

Online with Credit card Orders shipped same day!

*orders placed prior to 3:30pm EST

1-888-688-2188 (Toll free)

sales@coolgear.com