



12 Port USB 2.0 Powered Hub w/ Port Status LEDs



Industrial Grade | +7~24V DC Input | Surface Mountable | 480 Mbps | LED Indicators

Model No. USBG-12U2ML



- **High Speeds:** This USB hub is 2.0 compliant, ensuring fast 480Mbps data transfer speeds. It supports high speed and full speed which enables it to be compatible with USB 1.1.
- **Superior Build Quality:** Housed in a rugged steel chassis with built in mountable flanges, the 12-port hub is perfect for installations in offices, labs, warehouses, heavy machinery, automation equipment, and other industrial applications.
- **Check Your Ports' Status:** Quickly check the status of each port individually with built in LED indicators.
- **Upstream:** 1 USB port, Type B connector
- **Downstream:** 12 USB ports, Type A connectors
- **Power Connector:** 3-Pin Terminal Block
- **Mounting Options:** Wall & Surface

Interested? [LEARN MORE →](#)



[View more images here >](#)

Questions? Speak to an engineering expert today!

Our on site engineers are ready to help you with your build.

☎ [1-727-209-1300](tel:1-727-209-1300) (Local) ✉ expert@coolgear.com



We Speak Your Speak - When you reach out to our support, you'll find yourself in the hands of a solution-oriented, knowledgeable expert ready to answer whatever question you throw at them. Go ahead, test us.

We're Ready For Integration, Every Time. - Coolgear streamlines the task of selecting charging and connectivity products. For over 20 years our rugged, off-the-shelf USB hubs and serial products are ready to go for your next project.

Within every great machine, lives Coolgear. - At Coolgear, we're just as passionate about building great products as you are. That's why we aim to meet or exceed your build specs every time.,

Advanced Engineering - Coolgear painstakingly sources high-quality components, oversees all manufacturing methods, and conducts rigorous testing to ensure all our products are industrial-grade. This means greater duty cycle, zero data loss, and longer lasting builds. We promise.,

PRODUCT SPECIFICATIONS

Looking for product documentation?

[View CAD Models, Data sheet and Drawings here >](#)



Environmental	Operating Temperature	0°C to 55°C (32°F to 131°F)
	Storage Temperature	-20°C to 85°C (-4°F to 185°F)
	Humidity	5% ~ 95% (non-condensing)
Performance	Max Data Transfer Rate	480Mbps
	Over Current Protection	Y
Hardware	Chipset	GL 852G
	LED Indicators	Port Status, Power
Product Information	Warranty	1 year from date of purchase
	Input Voltage	+7~24V DC
Power	Over Current Protection	Y
	Power Source	3-Pin Terminal Block, AC Adapter Not Included
	Idle Consumption	23mA @ 12V Terminal Power
	External Power Required	Yes
Software	OS Support	Win 11, Linux, Mac OSX, Win 10, Win 7, Win 8
What's in the Box	Package Contents	3-Pin Terminal Block, Hub, Mounting Plate, Screw Pack, USB-A to USB-B Cable
	USB Type	USB 2.0
USB	Upstream USB Ports	1 Type-B Female USB
	Downstream USB Ports	12 Type-A Female USB
	Color	Black
	Item Dimensions (L x W x H)	6.25 (5.250 w/flange) x 2.60 x 2.00 in.
Mechanical	Item Weight	0.843 lbs.
	Mounting Style	Surface / Wall Mount, Din-Rail Mount
	Ports	12 USB Ports
	Material of Construction	Galvanized Steel
Compliance	Country of Origin	Taiwan
	Certifications	REACH, RoHS
	UPC	729440625146
Other Data	Series	DRS-UH (DIN-Rail Series Hubs)
	Weight	1.2 lbs
	Dimensions	8.5 x 5.5 x 2.25 in

Ready to Buy? Let's get to work!

Purchase order lets set you up.

Online with Credit card Orders shipped same day!

*orders placed prior to 3:30pm EST

1-888-688-2188 (Toll free)

sales@coolgear.com