4 Port USB 2.0 Powered Hub w/ Port Status LEDs

Industrial Grade | +7~24V DC Input | Surface Mountable | DIN Rail | 480 Mbps | LED Indicators

Model No. **USBG-4U2ML**

View more images here >

- **High Speeds:** This USB hub is 2.0 compliant, ensuring fast 480Mbps data transfer speeds. It supports high speed and full speed which enables it to be compatible with USB 1.1.
- **Superior Build Quality:** Housed in a rugged steel chassis with built in mountable flanges, the 4-port hub is perfect for installations in offices, labs, warehouses, heavy machinery, automation equipment, and other industrial applications.
- **Check Your Ports' Status:** Quickly check the status of each port individually with built in LED indicators.
- **Upstream:** 1 USB port, Type B connector
- **Downstream:** 4 USB ports, Type A connectors
- **Power Connector:** 2-Pin Terminal Block
- **Mounting Options:** Wall, Surface, and DIN Rail
- **Supply Current:** 900mA USB Bus Power for Each Downstream Port

Interested? LEARN MORE →

Questions? Speak to an engineering expert today!

Our on site engineers are ready to help you with your build.

1-727-209-1300 (Local) expert@coolgear.com

We Speak Your Speak - When you reach out to our support, you'll find yourself in the hands of a solution-oriented, knowledgeable expert ready to answer whatever question you throw at them. Go ahead, test us.

We're Ready For Integration, Every Time. - Coolgear streamlines the task of selecting charging and connectivity products. For over 20 years our rugged, off-the-shelf USB hubs and serial products are ready to go for your next project.

Within every great machine, lives Coolgear. - At Coolgear, we're just as passionate about building great products as you are. That's why we aim to meet or exceed your build specs every time.,

Advanced Engineering - Coolgear painstakingly sources high-quality components, oversees all manufacturing methods, and conducts rigorous testing to ensure all our products are industrial-grade. This means greater duty cycle, zero data loss, and longer lasting builds. We promise.,

PRODUCT SPECIFICATIONS

Looking for product documentation?
View CAD Models, Data sheet and Drawings here >

Environmental	**Operating Temperature**	0°C to 55°C (32°F to 131°F)
	Storage Temperature	-20°C to 85°C (-4°F to 185°F)
	Humidity	5% ~ 95% (non-condensing)
Performance	**Max Data Transfer Rate**	480Mbps
Hardware	**Chipset**	NEC D720114
	Charging Protocols	Dedicated Charging Port (DCP)
	LED Indicators	Port Status, Power
	Per USB Port Current	900mA maximum
Product Information	**Warranty**	1 year from date of purchase
Power	**Input Voltage**	+7~24V DC
	Power Source	3-Pin Terminal Block, AC Adapter Not Included
	Idle Consumption	14mA @ 12V Terminal Power, 18mA Bus powered
	External Power Required	No
Software	**OS Support**	Win 11, Linux, Mac OSX, Win 10, Win 7, Win 8
What's in the Box	**Package Contents**	DIN Rail Clip(s), Hub, Screw Pack, USB-A to USB-B Cable
USB	**USB Type**	USB 2.0
	Upstream USB Ports	1 Type-B Female USB
	Downstream USB Ports	4 Type-A Female USB
Mechanical	**Color**	Black
	Item Dimensions (L × W × H)	4.50 × 2.26 × 1.03 in.
	Item Weight	0.45 lbs.
	Mounting Style	Surface / Wall Mount, Din-Rail Mount
	Ports	4 USB Ports
	Material of Construction	Galvanized Steel
Compliance	**Certifications**	TAA Hubs, CE, FCC, RoHS
Other Data	**UPC**	729440625122
	Series	DRS-UH (DIN-Rail Series Hubs)
	Weight	.85 lbs
	Dimensions	9 × 6.25 × 1.75 in

Ready to Buy? Let's get to work!

Purchase order lets set you up.

Online with Credit card Orders shipped same day!

*orders placed prior to 3:30pm EST

1-888-688-2188 (Toll free)

sales@coolgear.com