

# 4 Port USB 2.0 Powered Hub w/ Port Status LEDs



Industrial Grade | +7~24V DC Input | Surface Mountable | DIN Rail | 480 Mbps | LED Indicators

Model No. USBG-4U2ML



- **High Speeds:** This USB hub is 2.0 compliant, ensuring fast 480Mbps data transfer speeds. It supports high speed and full speed which enables it to be compatible with USB 1.1.
- Superior Build Quality: Housed in a rugged steel chassis with built in mountable flanges, the 4-port hub is perfect for installations in offices, labs, warehouses, heavy machinery, automation equipment, and other industrial applications.
- Check Your Ports' Status: Quickly check the status of each port individually with built in LED indicators.
- Upstream: 1 USB port, Type B connector
- **Downstream:** 4 USB ports, Type A connectors
- Power Connector: 2-Pin Terminal Block

Interested? LEARN MORE >

- Mounting Options: Wall, Surface, and DIN Rail
- Supply Current: 900mA USB Bus Power for Each Downstream Port





## Questions? Speak to an engineering expert today!

Our on site engineers are ready to help you with your build.

<sup>1</sup> 1-727-209-1300 (Local) **expert@coolgear.com** 



We Speak Your Speak - When you reach out to our support, you'll find yourself in the hands of a solution-oriented, knowledgeable expert ready to answer whatever question you throw at them. Go ahead, test us.

We're Ready For Integration, Every Time. - Coolgear streamlines the task of selecting charging and connectivity products. For over 20 years our rugged, off-the-shelf USB hubs and serial products are ready to go for your next project.

**Within every great machine, lives Coolgear.** - At Coolgear, we're just as passionate about building great products as you are. That's why we aim to meet or exceed your build specs every time.,

**Advanced Engineering** - Coolgear painstakingly sources high-quality components, oversees all manufacturing methods, and conducts rigorous testing to ensure all our products are industrial-grade. This means greater duty cycle, zero data loss, and longer lasting builds. We promise.,

#### **PRODUCT SPECIFICATIONS**

#### Looking for product documentation?

View CAD Models, Data sheet and Drawings here >



Operating Temperature 0°C to 55°C (32°F to 131°F)

**Environmental Storage Temperature** -20°C to 85°C (-4°F to 185°F)

> **Humidity** 5% ~ 95% (non-condensing)

**Performance Max Data Transfer Rate** 480Mbps

> Chipset NEC D720114

**Charging Protocols** Dedicated Charging Port (DCP) **Hardware** 

**LED Indicators** Port Status, Power **Per USB Port Current** 900mA maximum

**Product** 

1 year from date of purchase Warranty Information

> **Input Voltage** +7~24V DC

**Power Source** 3-Pin Terminal Block, AC Adapter Not Included **Power** 

**Idle Consumption** 14mA @ 12V Terminal Power, 18mA Bus powered

External Power Required No

**Software OS Support** Win 11, Linux, Mac OSX, Win 10, Win 7, Win 8

What's in the Box Package Contents DIN Rail Clip(s), Hub, Screw Pack, USB-A to USB-B Cable

> **USB 2.0 USB Type**

**USB Upstream USB Ports** 1 Type-B Female USB

> **Downstream USB Ports** 4 Type-A Female USB

Color Black

Item Dimensions (L × W ×

H)

 $4.50 \times 2.26 \times 1.03$  in.

Mechanical **Item Weight** 0.45 lbs.

> **Mounting Style** Surface / Wall Mount, Din-Rail Mount

4 USB Ports **Ports** Material of Construction Galvanized Steel

Compliance Certifications TAA Hubs, CE, FCC, RoHS

> **UPC** 729440625122

**Series** DRS-UH (DIN-Rail Series Hubs) **Other Data** 

Weight .85 lbs

**Dimensions**  $9 \times 6.25 \times 1.75$  in

### Ready to Buy? Let's get to work!

Purchase order lets set you up.

Online with Credit card Orders shipped same day!

\*orders placed prior to 3:30pm EST

1-888-688-2188 (Toll free)

sales@coolgear.com