

4 Port Industrial USB 3.2 Gen 2 Type-C Hub w/ Screw-Locking Ports & Status LEDs



Industrial Grade | +7~48V DC Input | Surface Mountable | 10 Gbps | Screw Lock

Model No. CG-4PG2MHUB





- Super Fast Speeds: This USB hub is 3.2 Gen 2 compliant, ensuring super-fast 10Gbps data transfer speeds. It supports super speed +, high speed and full speed which enables it to be compatible with USB 3.2 Gen 1 / 2.0 / 1.1.
- Superior Build Quality: Housed in a rugged steel chassis with built in mountable flanges, the 4-port hub is perfect for workstations installations in offices, labs, warehouses, and other industrial applications.
- Check Your Ports' Status: Quickly check the status of each port individually with built in LED indicators.
- Upstream: 1 USB port, Type C connector, Screw-lock type
- Downstream: 2 USB ports, Type C connectors, Screw-lock type & 2 USB ports, Type A connectors, Screw-lock type
- Power Connector: 2-Pin Terminal Block
- **LED Indicators:** 4 LEDs for each downstream port to indicate the current bus
- Mounting Options: Wall, Surface, & DIN Rail

Interested? LEARN MORE >

Questions? Speak to an engineering expert today!

Our on site engineers are ready to help you with your build.

¹ 1-727-209-1300 (Local) **expert@coolgear.com**



We Speak Your Speak - When you reach out to our support, you'll find yourself in the hands of a solution-oriented, knowledgeable expert ready to answer whatever question you throw at them. Go ahead, test us.

We're Ready For Integration, Every Time. - Coolgear streamlines the task of selecting charging and connectivity products. For over 20 years our rugged, off-the-shelf USB hubs and serial products are ready to go for your next project.

Within every great machine, lives Coolgear. - At Coolgear, we're just as passionate about building great products as you are. That's why we aim to meet or exceed your build specs every time.,

Advanced Engineering - Coolgear painstakingly sources high-quality components, oversees all manufacturing methods, and conducts rigorous testing to ensure all our products are industrial-grade. This means greater duty cycle, zero data loss, and longer lasting builds. We promise.,

PRODUCT SPECIFICATIONS

Looking for product documentation?

View CAD Models, Data sheet and Drawings here >



Operating Temperature 0°C to 70°C (32°F to 158°F)

Humidity 5% ~ 95% (non-condensing)

Max Data Transfer Rate 10Gbps
Performance

Over Current Protection Y

Chipset VL820-Q8

Apple 2.4A, BC 1.2, Charging Downstream Port (CDP),

Hardware Charging Protocols Dedicated Charging Port (DCP), Samsung, Standard

Downstream Port (SDP)

LED Indicators Port Status, Power

Product

Warranty 1 year from date of purchase

Input Voltage +7~48V DC

Over Current Protection Y
Power

Power Source 2-Pin Terminal Block, AC Adapter Not Included

External Power Required No

Software OS Support Win 11, Linux, Mac OSX, Win 10, Win 7, Win 8

What's in the Box Package Contents

2-Pin Terminal Block, DIN Rail Clip(s), Hub, Mounting Plate,

Screw Pack, USB-C to Screw Lock USB-C Cable

USB Type USB 3.2 Gen 2

Upstream USB Ports 1 Type-C Female USB USB

Downstream USB Ports 2 Type-A Female USB, 2 Type-C Female USB

Screw Lock Compatible Yes

Color White

Item Dimensions (L × W ×

H)

 $5.2 \times 2.42 \times 1.43$ in.

Mechanical Item Weight 0.637 lbs.

Mounting Style Surface / Wall Mount, Din-Rail Mount

Ports 4 USB Ports

Material of Construction Galvanized Steel

Compliance Country of Origin Taiwan
Certifications RoHS

UPC 045079161023

Other Data

Series

DRS-UH (DIN-Rail Series Hubs)

Weight 1.16 lbs

Dimensions 9.500 × 6.625 × 2.250 in

Ready to Buy? Let's get to work!

Purchase order lets set you up.

Online with Credit card Orders shipped same day!

1-888-688-2188 (Toll free)