



7 Port USB 2.0 Hub w/ Screw Locking Ports



Industrial Grade | +7~24V DC Input | Surface Mountable | DIN Rail | 480 Mbps | Screw Lock

Model No. USBG-7DU2



- **High Speeds:** This USB hub is 2.0 compliant, ensuring fast 480Mbps data transfer speeds. It supports high speed and full speed which enables it to be compatible with USB 1.1.
- **Superior Build Quality:** Housed in a rugged steel chassis with built in mountable flanges, the 7-port hub is perfect for installations in offices, labs, warehouses, heavy machinery, automation equipment, and other industrial applications.
- **Secure Connections:** Each port features a screw locking for safe and secure USB connections.
- **Upstream:** 1 USB port, Type B connector, Screw-lock type
- **Downstream:** 7 USB ports, Type A connectors, Screw-lock type
- **Power Connector:** 2-Pin Terminal Block
- **Mounting Options:** Wall, Surface, & DIN Rail

Interested? [LEARN MORE →](#)



[View more
images here >](#)

Questions? Speak to an engineering expert today!

Our on site engineers are ready to help you with your build.

☎ [1-727-209-1300](tel:1-727-209-1300) (Local) ✉ expert@coolgear.com



We Speak Your Speak - When you reach out to our support, you'll find yourself in the hands of a solution-oriented, knowledgeable expert ready to answer whatever question you throw at them. Go ahead, test us.

We're Ready For Integration, Every Time. - Coolgear streamlines the task of selecting charging and connectivity products. For over 20 years our rugged, off-the-shelf USB hubs and serial products are ready to go for your next project.

Within every great machine, lives Coolgear. - At Coolgear, we're just as passionate about building great products as you are. That's why we aim to meet or exceed your build specs every time.,

Advanced Engineering - Coolgear painstakingly sources high-quality components, oversees all manufacturing methods, and conducts rigorous testing to ensure all our products are industrial-grade. This means greater duty cycle, zero data loss, and longer lasting builds. We promise.,

PRODUCT SPECIFICATIONS

Looking for product documentation?

[View CAD Models, Data sheet and Drawings here >](#)



Environmental	Operating Temperature	0°C to 55°C (32°F to 131°F)
	Storage Temperature	-20°C to 85°C (-4°F to 185°F)
	Humidity	5% ~ 95% (non-condensing)
Performance	Max Data Transfer Rate	480Mbps
	Over Current Protection	Y
	Over Voltage Protection	Y per buck
Hardware	Chipset	NEC D720113GK
	Charging Protocols	Dedicated Charging Port (DCP)
	LED Indicators	Power
Product Information	Warranty	1 year from date of purchase
	Input Voltage	+7~24V DC
	Over Current Protection	Y
Power	Over Voltage Protection	Y per buck
	Power Source	2-Pin Terminal Block, AC Adapter Not Included
	Idle Consumption	23.82mA Bus Powered, 36.7 mA @ 12V Terminal Power
Software	External Power Required	No
	OS Support	OS Independent; No Additional Drivers Required
	Package Contents	DIN Rail Clip(s), Hub, Screw Lock USB-A to Screw Lock USB-B Cable, Screw Pack
What's in the Box	USB Type	USB 2.0
	Upstream USB Ports	1 Type-B Female USB
	Downstream USB Ports	7 Type-A Female USB
USB	Screw Lock Compatible	Yes
	Color	Black
	Item Dimensions (L x W x H)	5.2 x 2.42 x 1.43 in.
Mechanical	Item Weight	0.625 lbs.
	Mounting Style	Surface / Wall Mount, Din-Rail Mount
	Ports	7 USB Ports
Compliance	Material of Construction	Galvanized Steel
	Country of Origin	Taiwan
	Certifications	TAA Hubs , RoHS
Other Data	UPC	736983901422
	Series	DRS-UH (DIN-Rail Series Hubs)
	Weight	1.15 lbs
	Dimensions	11 x 6.25 x 2 in

Ready to Buy? Let's get to work!

1-888-688-2188 (Toll free)

Purchase order lets set you up.
Coolgear | Charging & Connectivity Experts
www.coolgear.com

Visit coolgear.com/support for any questions & inquiries.

Online with Credit card Orders shipped same day!

 sales@coolgear.com

*orders placed prior to 3:30pm EST