

7 Port USB 2.0 Slim Powered Hub w/ Power Adapter



Industrial Grade | +5V DC Input | Surface Mountable | 480 Mbps

Model No. USBG-7U2ML



- **High Speeds:** This USB hub is 2.0 compliant, ensuring fast 480Mbps data transfer speeds. It supports high speed and full speed which enables it to be compatible with USB 1.1.
- Superior Build Quality: Housed in a rugged steel chassis with built in mountable flanges, the 7-port hub is perfect for installations in offices, labs, warehouses, heavy machinery, automation equipment, and other industrial applications.
- Power Your Way: The 7-port hub works in either buspowered mode or self-powered mode with the included power adapter.
- Upstream: 1 USB port, Type B connector
- Downstream: 7 USB ports, Type A connectors
- Power Connector: DC Barrel Jack, 4-Pin Aux Power Connector
- Mounting Options: Wall & Surface

View more images here >

Interested? LEARN MORE >

Questions? Speak to an engineering expert today!

Our on site engineers are ready to help you with your build.

¹ 1-727-209-1300 (Local) **expert@coolgear.com**



We Speak Your Speak - When you reach out to our support, you'll find yourself in the hands of a solution-oriented, knowledgeable expert ready to answer whatever question you throw at them. Go ahead, test us.

We're Ready For Integration, Every Time. - Coolgear streamlines the task of selecting charging and connectivity products. For over 20 years our rugged, off-the-shelf USB hubs and serial products are ready to go for your next project.

Within every great machine, lives Coolgear. - At Coolgear, we're just as passionate about building great products as you are. That's why we aim to meet or exceed your build specs every time.,

Advanced Engineering - Coolgear painstakingly sources high-quality components, oversees all manufacturing methods, and conducts rigorous testing to ensure all our products are industrial-grade. This means greater duty cycle, zero data loss, and longer lasting builds. We promise.,

PRODUCT SPECIFICATIONS

Looking for product documentation?

View CAD Models, Data sheet and Drawings here >



Operating Temperature 0°C to 55°C (32°F to 131°F)

Environmental Storage Temperature -20 to 75°C (-4 to 167°F)

Humidity 5% ~ 95% (non-condensing)

Performance Max Data Transfer Rate 480Mbps

Chipset FE2.1

Charging Protocols Dedicated Charging Port (DCP) **Hardware**

LED Indicators Power **Per USB Port Current** 1.5 A

Product Information

Warranty 1 year from date of purchase

Input Voltage +5V DC

Power Source4-Pin Aux Power Connector, AC Adapter Included, DC Barrel

Jack 2.5mm ID × 5.5mm OD

Idle Consumption3.26mA Bus Powered, 3.63mA @ 5V Terminal Power

Power Adapter Input Current 0.58A

Adapter Input Voltage 100~240V AC

Adapter Output Current 4A
Adapter Output Voltage 5V DC
External Power Required No

Software OS Support Win 11, Linux, Mac OSX, Win 10, Win 7, Win 8

What's in the Box Package Contents Hub, Power Adapter, USB-A to USB-B Cable

USB Type USB 2.0

USB Upstream USB Ports 1 Type-B Female USB

Downstream USB Ports 7 Type-A Female USB

Color Black

Item Dimensions (L × W ×

H)

 $6.01 (7.01 \text{ w/flange}) \times 2.35 \times 0.91 \text{ in.}$

Mechanical Item Weight 0.612 lbs.

Mounting Style Surface / Wall Mount

Ports 7 USB Ports

Material of Construction Galvanized Steel

Compliance Country of Origin Taiwan
Certifications RoHS

UPC 729440625139

Series WKS-UH (Workstation Series Hubs)
Other Data

Weight 1.8 lbs

Dimensions $11.5 \times 7.5 \times 2.75 \text{ in}$

Ready to Buy? Let's get to work!

Online with Credit card Orders shipped same day!

*orders placed prior to 3:30pm EST

*orders placed prior to 3:30pm EST