



Mini Nest Cam IQ PoE PRO Install Kit (Active PoE Pod + Active PoE Injector Included) Version 2



USB Type-C PoE AC/DC Converter

Model No. CG-POE15VPDv2-KIT



Coolgear's newest USB Type-C PoE adapter works with a Cat5/6 cable from a PoE injector connected to its RJ45 port. This extends the length of power to the Nest Cam IQ Indoor Gen 1 or Nest Cam IQ Outdoor Gen 1 by up to 100 meters from a power source. Use the Type-C USB port to connect the Nest Cam.

- Utilizes a PoE injector for power.
- Specifically designed for the 15V power needed for the Nest Cam IQ Indoor and Outdoor versions Gen 1
- Overload & short-circuit protection.
- Fully IEEE802.3at and IEEE802.3af compliant PoE.

Interested? [LEARN MORE →](#)



[View more images here >](#)

Questions? Speak to an engineering expert today!

Our on site engineers are ready to help you with your build.

☎ [1-727-209-1300](tel:1-727-209-1300) (Local) ✉ expert@coolgear.com



We Speak Your Speak - When you reach out to our support, you'll find yourself in the hands of a solution-oriented, knowledgeable expert ready to answer whatever question you throw at them. Go ahead, test us.

We're Ready For Integration, Every Time. - Coolgear streamlines the task of selecting charging and connectivity products. For over 20 years our rugged, off-the-shelf USB hubs and serial products are ready to go for your next project.

Within every great machine, lives Coolgear. - At Coolgear, we're just as passionate about building great products as you are. That's why we aim to meet or exceed your build specs every time.,

Advanced Engineering - Coolgear painstakingly sources high-quality components, oversees all

manufacturing methods, and conducts rigorous testing to ensure all our products are industrial-grade. This

Coolgear | Charging & Connectivity Experts
www.coolgear.com

Visit coolgear.com/support for any questions & inquiries.

means greater duty cycle, zero data loss, and longer lasting builds. We promise.,

PRODUCT SPECIFICATIONS

Looking for product documentation?
[View CAD Models, Data sheet and Drawings here >](#)



Environmental	Operating Temperature	Maximum Ambient Operating Temp. of 78°C
	Isolated/Surge Protected	Y
Performance	Over Current Protection	Y
	Over Voltage Protection	Y
Power	Over Current Protection	Y
	Over Voltage Protection	Y
PD Profile Support	Voltage Profiles	15V
USB	Isolated/Surge Protected	Y
	Color	White
Mechanical	Item Dimensions (L × W × H)	54x 29x25mm (LxWxH)
	UPC	045079161344
Other Data	Weight	1.18 lbs
	Dimensions	2.250 × 1.250 × 1.250 in

Ready to Buy? Let's get to work!

Purchase order lets set you up.

Online with Credit card Orders shipped same day!

*orders placed prior to 3:30pm EST

 [1-888-688-2188 \(Toll free\)](tel:1-888-688-2188)

 sales@coolgear.com