



# PoE Voltage Monitor for STD PoE and Non-STD PoE



## PoE Voltage Monitoring

Model No. POEPDPM4



Confirm your PoE standard and Non-standard voltages from 36V to 60V applications. Compliant with 802.3 af, at, bt type3 & 4 standard PoE. This is a great diagnostic tool for network installers that work with PoE.

- Verifies the presence of proper voltage for both the active and passive PoE applications.
- Voltage range: 36V to 60V for standard PoE and 9V (blue LED) / 12V (red LED) to 60V for Non-standard PoE.
- Verifies the PSE is delivering proper power compliant with alternative A or B or both 4-pair mode in 802.3 af or at/bt standard.
- Verifies the presence of proper voltage for both the active and passive PoE applications.

**Interested? LEARN MORE →**



[View more images here >](#)

## Questions? Speak to an engineering expert today!

Our on site engineers are ready to help you with your build.

☎ [1-727-209-1300](tel:1-727-209-1300) (Local) ✉ [expert@coolgear.com](mailto:expert@coolgear.com)



**We Speak Your Speak** - When you reach out to our support, you'll find yourself in the hands of a solution-oriented, knowledgeable expert ready to answer whatever question you throw at them. Go ahead, test us.

**We're Ready For Integration, Every Time.** - Coolgear streamlines the task of selecting charging and connectivity products. For over 20 years our rugged, off-the-shelf USB hubs and serial products are ready to go for your next project.

**Within every great machine, lives Coolgear.** - At Coolgear, we're just as passionate about building great products as you are. That's why we aim to meet or exceed your build specs every time.,

**Advanced Engineering** - Coolgear painstakingly sources high-quality components, oversees all manufacturing methods, and conducts rigorous testing to ensure all our products are industrial-grade. This means greater duty cycle, zero data loss, and longer lasting builds. We promise.,

# PRODUCT SPECIFICATIONS

Looking for product documentation?  
[View CAD Models, Data sheet and Drawings here >](#)




Power	Input Voltage	Max 36V to 60V
	Adapter Power	PoE
	Color	White
Mechanical	Item Dimensions (L x W x H)	3.9 x 1.4 x 1in (LxWxH)
	Item Weight	0.2 lbs
	Country of Origin	Taiwan
Compliance	Certifications	<a href="#">CE</a> , <a href="#">FCC</a> , <a href="#">RoHS</a>
	Ethernet Compliance	IEEE 802.3 af, IEEE 802.3 at, IEEE 802.3 bt type3
	UPC	045079161269
Other Data	Connector	RJ45
	Weight	0.2 lbs
	Dimensions	2.77 x 1.77 x 6.10 in


### Ready to Buy? Let's get to work!

**Purchase order** lets set you up.

**Online with Credit card** Orders shipped same day!

\*orders placed prior to 3:30pm EST

 **1-888-688-2188 (Toll free)**

 **sales@coolgear.com**