

# PoE Voltage Monitor for STD PoE and Non-STD PoE



PoE Voltage Monitoring

#### Model No. POEPDPM4



- Verifies the presence of proper voltage for bothe active and passive PoE applications.
- Voltage range: 36V to 60V for standard PoE and 9V (blue LED) / 12V (red LED) to 60V for Non-standard PoE.
- Verifies the PSE is delivering proper power compliant with alternative A or B or both 4-pair mode in 802.3 af or at/bt standard.
- Verifies the presence of proper voltage for bothe active and passive PoE applications.

### Interested? LEARN MORE →



## **Ouestions?** Speak to an engineering expert today!

Our on site engineers are ready to help you with your build.

<sup>ℓ</sup> 1-727-209-1300 (Local) <sup>∞</sup> expert@coolgear.com



We Speak Your Speak - When you reach out to our support, you'll find yourself in the hands of a solutionoriented, knowledgeable expert ready to answer whatever question you throw at them. Go ahead, test us. We're Ready For Integration, Every Time. - Coolgear streamlines the task of selecting charging and connectivity products. For over 20 years our rugged, off-the-shelf USB hubs and serial products are ready to go for your next project.

Within every great machine, lives Coolgear. - At Coolgear, we're just as passionate about building great products as you are. That's why we aim to meet or exceed your build specs every time.,

**Advanced Engineering** - Coolgear painstakingly sources high-quality components, oversees all manufacturing methods, and conducts rigorous testing to ensure all our products are industrial-grade. This means greater duty cycle, zero data loss, and longer lasting builds. We promise.,

## PRODUCT SPECIFICATIONS



| Power      | Input Voltage                  | Max 36V to 60V                                    |
|------------|--------------------------------|---|
|            | Adapter Power                  | РоЕ   |
| Mechanical | Color                          | White   |
|            | Item Dimensions (L × W =<br>H) | <b>*</b> 3.9 x 1.4 x 1in (LxWxH)                  |
|            | Item Weight                    | 0.2 lbs   |
| Compliance | Country of Origin              | Taiwan  |
|            | Certifications                 | <u>CE, FCC, RoHS</u>                              |
|            | Compliance                     | IEEE 802.3 af, IEEE 802.3 at, IEEE 802.3 bt type3 |
| Other Data | UPC                            | 045079161269                                      |
|            | Connector                      | RJ45  |
|            | Weight                         | 0.2 lbs   |
|            | Dimensions                     | 2.77 × 1.77 × 6.10 in                             |

### Ready to Buy? Let's get to work!

Purchase order lets set you up. Online with Credit card Orders shipped same day! \*orders placed prior to 3:30pm EST <sup>(</sup> <u>1-888-688-2188 (Toll free)</u>

sales@coolgear.com