



RS232/422/485 to USB 2.0 Serial Adapter Combo



Serial to USB Multi-Protocol Adapter

Model No. CG-232485CBO



This 2-Port serial adapter supports the use of one or two serial protocols simultaneously making it very versatile for many COM applications.

- Option to make use of one, or two Serial Protocols simultaneously.
- DIP Switch control for RS-232, RS422, or RS485 signal usage.
- LED status indicators for RX/TX and which protocol used.
- Mountable to any flat surface for application stability.

Interested? [LEARN MORE →](#)



[View more
images here >](#)

Questions? Speak to an engineering expert today!

Our on site engineers are ready to help you with your build.

☎ [1-727-209-1300](tel:1-727-209-1300) (Local) ✉ expert@coolgear.com



We Speak Your Speak - When you reach out to our support, you'll find yourself in the hands of a solution-oriented, knowledgeable expert ready to answer whatever question you throw at them. Go ahead, test us.

We're Ready For Integration, Every Time. - Coolgear streamlines the task of selecting charging and connectivity products. For over 20 years our rugged, off-the-shelf USB hubs and serial products are ready to go for your next project.

Within every great machine, lives Coolgear. - At Coolgear, we're just as passionate about building great products as you are. That's why we aim to meet or exceed your build specs every time.,

Advanced Engineering - Coolgear painstakingly sources high-quality components, oversees all manufacturing methods, and conducts rigorous testing to ensure all our products are industrial-grade. This means greater duty cycle, zero data loss, and longer lasting builds. We promise.,

PRODUCT SPECIFICATIONS

Looking for product documentation?
[View CAD Models, Data sheet and Drawings here >](#)



Physical Characteristics	Compliance	Country of Origin	Taiwan
		Color	Black
		Mounting Style	Surface Mount
		Ports	1 USB Port
Serial Attributes		Screw Lock Compatible	Yes
		Serial Standards	RS232, RS422, RS485
		Baud Rate	921.6K bps
Software		OS Support	Win-2000, Win XP, Win Vista, Win 7, Win 8, Win 10, Linux, Mac OSX
	Environmental	Operating Temperature	0C to 55C
Hardware		Chipset	FTDI
		Upstream USB Ports	1 Type-B Female USB
		Connector	DB9
Other Data		USB Interface	USB 2.0
		Weight	1.002 lbs
		Dimensions	9.00 × 6.250 × 1.687 in

Ready to Buy? Let's get to work!

Purchase order lets set you up.

Online with Credit card Orders shipped same day!

*orders placed prior to 3:30pm EST

📞 [1-888-688-2188](tel:1-888-688-2188) (Toll free)

✉️ sales@coolgear.com