

USB 2.0 to RS-232 / RS-422 / RS-485 Selectable Industrial Serial Adapter w/ 15kV ESD Surge Protection



Model No. USBG-COMi-M







<u>View more</u> <u>images here ></u>

RS-232 | RS-422 | RS-485 | 512 Bytes Receive | 512 Bytes Transmit

- Superior Build Quality: Housed in a rugged steel chassis
 with built in mountable flanges, the serial adapter hub is
 perfect for installations in labs, warehouses, or heavy
 machinery.
- Safe Industrial Connections: Designed for use with Bar Code Scanners, Time Clocks, Label Printers, Point of Sale Terminals, Receipt Printers, and more the USB to Serial Adapter offers 15kV surge protection for connected devices.
- Effortless Port Configuration: The adapter is designed with external dip switches to set RS-232, RS-422 or RS-485 ports and different operation modes conveniently.
- **COM Retention:** COM Ports are fully configurable, and after reboots, port assignments are preserved.
- **USB Power:** Power is drawn from a USB connection, no bulky power supply or power outlet is required.
- Upstream: 1 USB port, Type B Female Connector
- Downstream: 1 Male DB9, w/ nuts, 1 6-pin Terminal Block
- LEDs: Power, TX / RX

Interested? LEARN MORE >

Questions? Speak to an engineering expert today!

Our on site engineers are ready to help you with your build.

1-727-209-1300 (Local)
 expert@coolgear.com



We Speak Your Speak - When you reach out to our support, you'll find yourself in the hands of a solution-oriented, knowledgeable expert ready to answer whatever question you throw at them. Go ahead, test us.

We're Ready For Integration, Every Time. - Coolgear streamlines the task of selecting charging and connectivity products. For over 20 years our rugged, off-the-shelf USB hubs and serial products are ready to go for your next project.

Within every great machine, lives Coolgear. - At Coolgear, we're just as passionate about building great products as you are. That's why we aim to meet or exceed your build specs every time.,

manufacturing methods, and conducts rigorous testing to ensure all our products are industrial-grade. This means greater duty cycle, zero data loss, and longer lasting builds. We promise.,	

PRODUCT SPECIFICATIONS

Serial Attributes

Looking for product documentation?

View CAD Models, Data sheet and Drawings here >



Operating Temperature 0C to 55C

Environmental Storage Temperature -20 to 75°C (-4 to 167°F)

Humidity 5% ~ 95% (non-condensing)

ESD Protection 15KV Surge Protection

Performance Isolated/Surge Protected Yes

Max Data Transfer Rate 480Mbps

Chipset FTDI Hardware

LED Indicators Power, TX / RX

Product Information Warranty 1 year from date of purchase

Adapter Output Current 150mA

Power Adapter Output Voltage 5V

External Power Required No

Software OS Support Win 11, Linux, Mac OSX, Win 10, Win 7, Win 8

Data-, Data+, GND, DCD, RxD, TxD, DTR, GND, DSR, RTS,

RS Signals CTS, RI, TxD-, TxD+, RxD+, RxD-, GND, TxD-, TxD+, RxD+,

RxD-, GND, RTS-, RTS+, CTS+, CTS-

Serial Standards RS232, RS422, RS485

Baud Rate 921.6K bps FIFO Receive 512 bytes

FIFO Transmit 512 bytes

Data Bits 5, 6, 7, 8

Parity None, Even, Odd, Mark, Space

Stop Bits 1, 1.5, 2

Flow Control Hardware (RTS, CTS), XON/XOFF

USB Type USB 2.0

USB Isolated/Surge Protected Yes

Screw Lock Compatible Yes
Color Black

Item Dimensions (L × W ×

H)

 $3.23 \times 2.99 \times 0.91$ in.

Mechanical Item Weight 0.293 lbs.

Mounting Style Din-Rail, Surface Mount

Ports 1 Serial Port

Material of Construction Steel

Country of Origin Taiwan

Certifications REACH, RoHS

Connector 6-Pin Terminal Block, DB9 Male w/ Nuts

Chip Model FT231XQ

Other Data UPC 729440690960

Weight .7 lbs

Dimensions $5 \times 4 \times 2.5 \text{ in}$

Purchase order lets set you up.

Online with Credit card Orders shipped same day!

*orders placed prior to 3:30pm EST

1-888-688-2188 (Toll free)

sales@coolgear.com